

App Access for Jira Cloud REST APIs

App access rule data blocking is an early access feature and subject to change. It is available only to participants in the [Early Access Program \(EAP\)](#).

In this document:

Blocked when app access rule applies	1
Jira Platform	1
Jira Software	25
Jira Service Management	30
Not blocked when an app access rule applies	34
Jira Platform	34
Jira Software	98
Jira Service Management	99
Service desk	101

Blocked when app access rule applies

These APIs are blocked when the admin turns on the app access rule. Apps using these APIs will no longer be able to access the content or perform the actions listed below.

Jira Platform

These APIs are used by all Jira products.

App migration (version 2)

Name	Description	API docs link
Bulk update custom field value	Sets the value for a set of custom fields.	PUT /rest/atlassian-connect/1/migration/field
Bulk update entity properties	Sets the value of entity properties by type.	PUT /rest/atlassian-connect/1/migration/properties/{entityType}

Get workflow transition rule configurations	Returns a list of transition rule configurations for a workflow.	POST /rest/atlassian-connect/1/migration/workflow/rule/search
---	--	---

App migration (version 3)

Name	Description	API docs link
Bulk update custom field value	Sets the value for a set of custom fields.	PUT /rest/atlassian-connect/1/migration/field
Bulk update entity properties	Sets the value of entity properties by type.	PUT /rest/atlassian-connect/1/migration/properties/{entityType}
Get workflow transition rule configurations	Returns a list of transition rule configurations for a workflow.	POST /rest/atlassian-connect/1/migration/workflow/rule/search

App properties (version 2)

Name	Description	API docs link
Get app properties	Returns a list of properties for an app.	GET /rest/atlassian-connect/1/addons/{addonKey}/properties
Delete app property	Deletes a property for an app.	DELETE /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}
Get app property	Returns a property for an app.	GET /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}
Set app property	Sets a property for an app.	PUT /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}
Delete app property (Forge)	Deletes a property for a Forge app.	DELETE /rest/forge/1/app/properties/{propertyKey}
Set app property (Forge)	Sets a property for a Forge app.	PUT /rest/forge/1/app/properties/{propertyKey}

App properties (version 3)

Name	Description	API docs link
Get app properties	Returns a list of properties for an app.	GET /rest/atlassian-connect/1/addons/{addonKey}/properties
Get app property	Returns a property for an app.	GET /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}
Set app property	Sets a property for an app.	PUT /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}

Delete app property	Deletes a property for an app.	DELETE /rest/atlassian-connect/1/addons/{addonKey}/properties/{propertyKey}
Set app property (Forge)	Sets a property for a Forge app.	PUT /rest/forge/1/app/properties/{propertyKey}
Delete app property (Forge)	Deletes a property for a Forge app.	DELETE /rest/forge/1/app/properties/{propertyKey}

Avatars (version 2)

Name	Description	API docs link
Get avatars	Returns the system and custom avatars for a project or issue type.	GET /rest/api/2/universal_avatar/type/{type}/owner/{entityId}
Load an avatar	Loads a custom avatar for a project or issue type, from the specified URL.	POST /rest/api/2/universal_avatar/type/{type}/owner/{entityId}
Get an avatar image by ID	Returns the project or issue type avatar image for an avatar image ID.	GET /rest/api/2/universal_avatar/view/type/{type}/avatar/{id}

Avatars (version 3)

Name	Description	API docs link
Get avatars	Returns the system and custom avatars for a project or issue type.	GET /rest/api/3/universal_avatar/type/{type}/owner/{entityId}
Load an avatar	Loads a custom avatar for a project or issue type, from the specified URL.	POST /rest/api/3/universal_avatar/type/{type}/owner/{entityId}
Get an avatar image by ID	Returns the project or issue type avatar image for an avatar image ID.	GET /rest/api/3/universal_avatar/view/type/{type}/avatar/{id}

Dynamic modules (version 2)

Name	Description	API docs link
Delete modules	Removes modules.	DELETE /rest/atlassian-connect/1/app/module/dynamic
Get modules	Returns a list of modules.	GET /rest/atlassian-connect/1/app/module/dynamic
Register modules	Sets modules.	POST /rest/atlassian-connect/1/app/module/dynamic

Dynamic modules (version 3)

Name	Description	API docs link
Get modules	Returns a list of modules.	GET /rest/atlassian-connect/1/app/module/dynamic
Register modules	Sets modules.	POST /rest/atlassian-connect/1/app/module/dynamic
Delete modules	Removes modules.	DELETE /rest/atlassian-connect/1/app/module/dynamic

Filter sharing (version 2)

Name	Description	API docs link
Get all the share permissions for a filter	Returns the details of the sharing permissions for a filter.	GET /rest/api/2/filter/{id}/permission
Add a share permission for a filter	Adds a share permission for a filter	POST /rest/api/2/filter/{id}/permission
Delete share permission	Deletes shared access from a filter.	DELETE /rest/api/2/filter/{id}/permission/{permissionId}
Returns a single share permission for a filter	Returns a share permission for a filter.	GET /rest/api/2/filter/{id}/permission/{permissionId}

Filter sharing (version 3)

Name	Description	API docs link
Get all the share permissions for a filter	Returns the details of the sharing permissions for a filter.	GET /rest/api/3/filter/{id}/permission
Add a share permission for a filter	Adds a share permission for a filter	POST /rest/api/3/filter/{id}/permission
Returns a single share permission for a filter	Returns a share permission for a filter.	GET /rest/api/3/filter/{id}/permission/{permissionId}
Delete share permission	Deletes shared access from a filter.	DELETE /rest/api/3/filter/{id}/permission/{permissionId}

Filters (version 2)

Name	Description	API docs link
Create a filter	Creates a filter.	POST /rest/api/2/filter
Get my filters	Returns a list of filters owned by the current user. Optionally can request favourites as well.	GET /rest/api/2/filter/my

Search for filters	Returns a list of filters, by matching ID or specific attributes.	GET /rest/api/2/filter/search
Reset columns for a filter	Resets the user's column configuration for the filter to the default.	DELETE /rest/api/2/filter/{id}/columns
Get columns for a filter	Returns the columns configured for a filter. Returns labels and values.	GET /rest/api/2/filter/{id}/columns
Set columns for a filter	Sets the columns for a filter.	PUT /rest/api/2/filter/{id}/columns
Remove filter as favorite	Removes a filter as a favorite for the current user.	DELETE /rest/api/2/filter/{id}/favourite
Add filter as favorite	Favorites a filter for the current user.	PUT /rest/api/2/filter/{id}/favourite
Change a filter owner	Changes the owner of the filter, by accountID.	PUT /rest/api/2/filter/{id}/owner

Filters (version 3)

Name	Description	API docs link
Create a filter	Creates a filter.	POST /rest/api/3/filter
Get my filters	Returns a list of filters owned by the current user. Optionally can request favourites as well.	GET /rest/api/3/filter/my
Search for filters	Returns a list of filters, by matching ID or specific attributes.	GET /rest/api/3/filter/search
Get columns for a filter	Returns the columns configured for a filter. Returns labels and values.	GET /rest/api/3/filter/{id}/columns
Set columns for a filter	Sets the columns for a filter.	PUT /rest/api/3/filter/{id}/columns
Reset columns for a filter	Resets the user's column configuration for the filter to the default.	DELETE /rest/api/3/filter/{id}/columns
Add filter as favorite	Favorites a filter for the current user.	PUT /rest/api/3/filter/{id}/favourite
Remove filter as favorite	Removes a filter as a favorite for the current user.	DELETE /rest/api/3/filter/{id}/favourite
Change a filter owner	Changes the owner of the filter, by accountID.	PUT /rest/api/3/filter/{id}/owner

Issue attachments (version 2)

Name	Description	API docs link
Get attachment content	Returns the contents of an attachment.	GET /rest/api/2/attachment/content/{id}
Get attachment thumbnail	Returns an attachment's thumbnail. This operation can be accessed anonymously.	GET /rest/api/2/attachment/thumbnail/{id}

Delete attachment	Removes an attachment from an issue. This operation can be accessed anonymously.	DELETE /rest/api/2/attachment/{id}
Get attachment metadata	Returns an attachment's metadata (but not the attachment itself); for example, the attachment's ID and name. This operation can be accessed anonymously.	GET /rest/api/2/attachment/{id}
Get all metadata for ZIP attachment	Returns an attachment's metadata (but not the attachment itself), whether or not it is in a ZIP archive; for example, the attachment's ID and name. This operation can be accessed anonymously.	GET /rest/api/2/attachment/{id}/expand/human
Get all metadata for ZIP attachment contents	Returns the metadata of attachments inside a ZIP archive (but not the attachments or ZIP archive); for example, each attachments ID and name. This operation can be accessed anonymously.	GET /rest/api/2/attachment/{id}/expand/raw
Add attachment for an issue	Adds one or more attachments to an issue.	POST /rest/api/2/issue/{issueIdOrKey}/attachments

Issue attachments (version 3)

Name	Description	API docs link
Get attachment content	Returns the contents of an attachment.	GET /rest/api/3/attachment/content/{id}
Get attachment thumbnail	Returns an attachment's thumbnail. This operation can be accessed anonymously.	GET /rest/api/3/attachment/thumbnail/{id}
Get attachment metadata	Returns an attachment's metadata (but not the attachment itself); for example, the attachment's ID and name. This operation can be accessed anonymously.	GET /rest/api/3/attachment/{id}
Delete attachment	Removes an attachment from an issue. This operation can be accessed anonymously.	DELETE /rest/api/3/attachment/{id}
Get all metadata for ZIP attachment	Returns an attachment's metadata (but not the attachment itself), whether or not it is in a ZIP archive; for example, the attachment's ID and name. This operation can be accessed anonymously.	GET /rest/api/3/attachment/{id}/expand/human
Get all metadata for ZIP attachment contents	Returns the metadata of attachments inside a ZIP archive (but not the attachments or ZIP archive); for example, each attachments ID and name. This operation can be accessed anonymously.	GET /rest/api/3/attachment/{id}/expand/raw
Add attachment for an issue	Adds one or more attachments to an issue.	POST /rest/api/3/issue/{issueIdOrKey}/attachments

Issue comment properties (version 2)

Name	Description	API docs link
Get comment property keys	Returns the keys of all the properties of a comment. This operation can be accessed anonymously.	GET /rest/api/2/comment/{commentId}/properties

Issue comment properties (version 3)

Name	Description	API docs link
Get comment property keys	Returns the keys of all the properties of a comment. This operation can be accessed anonymously.	GET /rest/api/3/comment/{commentId}/properties

Issue comments (version 2)

Name	Description	API docs link
Get comments	Returns a list of comments specified by comment IDs. This operation can be accessed anonymously.	POST /rest/api/2/comment/list
Get comments for an issue	Returns all comments for an issue.	GET /rest/api/2/issue/{issueIdOrKey}/comment
Add comment to an issue	Adds a comment to an issue.	POST /rest/api/2/issue/{issueIdOrKey}/comment
Delete comment for an issue	Deletes a comment for an issue.	DELETE /rest/api/2/issue/{issueIdOrKey}/comment/{id}
Get comment for an issue	Returns a comment for an issue.	GET /rest/api/2/issue/{issueIdOrKey}/comment/{id}
Update comment for an issue	Updates a comment for an issue.	PUT /rest/api/2/issue/{issueIdOrKey}/comment/{id}

Issue comments (version 3)

Name	Description	API docs link
------	-------------	---------------

Get comments	Returns a list of comments specified by comment IDs. This operation can be accessed anonymously.	POST /rest/api/3/comment/list
Get comments for an issue	Returns all comments for an issue.	GET /rest/api/3/issue/{issueIdOrKey}/comment
Add comment to an issue	Adds a comment to an issue.	POST /rest/api/3/issue/{issueIdOrKey}/comment
Get comment for an issue	Returns a comment for an issue.	GET /rest/api/3/issue/{issueIdOrKey}/comment/{id}
Update comment for an issue	Updates a comment for an issue.	PUT /rest/api/3/issue/{issueIdOrKey}/comment/{id}
Delete comment for an issue	Deletes a comment for an issue.	DELETE /rest/api/3/issue/{issueIdOrKey}/comment/{id}

Issue custom fields (apps) (version 2)

Name	Description	API docs link
Get selectable options from an issue field	Returns the selectable options (available for the current user) for a select list issue field.	GET /rest/api/2/field/{fieldKey}/option/suggestions/edit
Get options for a visible issue field	Returns the list of options that can be viewed by a user for a select list issue field.	GET /rest/api/2/field/{fieldKey}/option/suggestions/search
Replace issue field option	Deselects an issue-field select-list option from all issues where it's used, and optionally replaces it with another option.	DELETE /rest/api/2/field/{fieldKey}/option/{optionId}/issue
Update multiple app-owned custom fields	Updates the values of multiple custom fields created by the app.	POST /rest/api/2/app/field/value
Update a single app-owned custom field	Updates the value of a single custom field created by the app.	PUT /rest/api/2/app/field/{fieldIdOrKey}/value

Issue custom fields (apps) (version 3)

Name	Description	API docs link
------	-------------	---------------

Get selectable options from an issue field	Returns the selectable options (available for the current user) for a select list issue field.	GET /rest/api/3/field/{fieldKey}/option/suggestions/edit
Get options for a visible issue field	Returns the list of options that can be viewed by a user for a select list issue field.	GET /rest/api/3/field/{fieldKey}/option/suggestions/search
Replace issue field option	Deselects an issue-field select-list option from all issues where it's used, and optionally replaces it with another option.	DELETE /rest/api/3/field/{fieldKey}/option/{optionId}/issue
Update multiple app-owned custom fields	Updates the values of multiple custom fields created by the app.	POST /rest/api/3/app/field/value
Update a single app-owned custom field	Updates the value of a single custom field created by the app.	PUT /rest/api/3/app/field/{fieldIdOrKey}/value

Issue fields (version 2)

Name	Description	API docs link
Delete a custom field	Deletes a custom field. Doesn't matter whether it is in trash or not.	DELETE /rest/api/2/field/{id}

Issue fields (version 3)

Name	Description	API docs link
Delete a custom field	Deletes a custom field. Doesn't matter whether it is in trash or not.	DELETE /rest/api/3/field/{id}

Issue links (version 2)

Name	Description	API docs link
Create issue link	Creates a link between two issues and optionally add a comment to the originating (outward) issue to provide context or details about the link	POST /rest/api/2/issueLink
Delete issue link	Deletes an issue link.	DELETE /rest/api/2/issueLink/{linkId}
Get issue link	Returns an issue link.	GET /rest/api/2/issueLink/{linkId}

Issue links (version 3)

Name	Description	API docs link
Create issue link	Creates a link between two issues and optionally add a comment to the originating (outward) issue to provide context or details about the link	POST /rest/api/3/issueLink
Get issue link	Returns an issue link.	GET /rest/api/3/issueLink/{linkId}
Delete issue link	Deletes an issue link.	DELETE /rest/api/3/issueLink/{linkId}

Issue properties (version 2)

Name	Description	API docs link
Update bulk set of issues by properties	Sets or updates entity property values on up to 10,000 issues.	POST /rest/api/2/issue/properties
Update bulk set of issues by issues	Sets or updates entity property values on up to 100 issues in the request.	POST /rest/api/2/issue/properties/multi
Bulk delete issue property	Deletes a property value from multiple issues. The issues to be updated can be specified by the filter criteria.	DELETE /rest/api/2/issue/properties/{propertyKey}
Bulk set issue property	Sets a property value on multiple issues.	PUT /rest/api/2/issue/properties/{propertyKey}
Get issue property keys	Returns the URLs and keys of an issue's properties.	GET /rest/api/2/issue/{issueIdOrKey}/properties
Delete issue property	Deletes an issue's property.	DELETE /rest/api/2/issue/{issueIdOrKey}/properties/{propertyKey}
Get issue property	Returns the key and value of an issue's property.	GET /rest/api/2/issue/{issueIdOrKey}/properties/{propertyKey}
Set issue property	Sets the value of an issue's property. Use this to store custom data against an issue.	PUT /rest/api/2/issue/{issueIdOrKey}/properties/{propertyKey}

Issue properties (version 3)

Name	Description	API docs link
Update bulk set of issues by properties	Sets or updates entity property values on up to 10,000 issues.	POST /rest/api/3/issue/properties

Update bulk set of issues by issues	Sets or updates entity property values on up to 100 issues in the request.	POST /rest/api/3/issue/properties/multi
Bulk set issue property	Sets a property value on multiple issues.	PUT /rest/api/3/issue/properties/{propertyKey}
Bulk delete issue property	Deletes a property value from multiple issues. The issues to be updated can be specified by the filter criteria.	DELETE /rest/api/3/issue/properties/{propertyKey}
Get issue property keys	Returns the URLs and keys of an issue's properties.	GET /rest/api/3/issue/{issueIdOrKey}/properties
Get issue property	Returns the key and value of an issue's property.	GET /rest/api/3/issue/{issueIdOrKey}/properties/{propertyKey}
Set issue property	Sets the value of an issue's property. Use this to store custom data against an issue.	PUT /rest/api/3/issue/{issueIdOrKey}/properties/{propertyKey}
Delete issue property	Deletes an issue's property.	DELETE /rest/api/3/issue/{issueIdOrKey}/properties/{propertyKey}

Issue remote links (version 2)

Name	Description	API docs link
Delete remote issue link by global ID	Deletes the remote issue link from the issue using the link's global ID.	DELETE /rest/api/2/issue/{issueIdOrKey}/remotelink
Get remote issue links	Returns the remote issue links for an issue. If a global ID for a remote issue link is provided, then the record with that global ID is returned. If no global ID is provided, all remote issue links for the issue are returned.	GET /rest/api/2/issue/{issueIdOrKey}/remotelink
Create or update remote issue link	Creates or updates a remote issue link for a specific issue. If a `globalId` is given and a matching remote issue link is found, it is updated and any fields not included in the request are set to null. If no matching `globalId` is found, a new remote issue link is created.	POST /rest/api/2/issue/{issueIdOrKey}/remotelink
Delete remote issue link by ID	Deletes a remote issue link from an issue.	DELETE /rest/api/2/issue/{issueIdOrKey}/remotelink/{linkId}
Get remote issue link by ID	Returns a remote issue link for an issue.	GET /rest/api/2/issue/{issueIdOrKey}/remotelink/{linkId}
Update remote issue link by ID	Updates a remote issue link for an issue.	PUT /rest/api/2/issue/{issueIdOrKey}/remotelink/{linkId}

Issue remote links (version 3)

Name	Description	API docs link
Get remote issue links	Returns the remote issue links for an issue. If a global ID for a remote issue link is provided, then the record with that global ID is returned. If no global ID is provided, all remote issue links for the issue are returned.	GET /rest/api/3/issue/{issueIdOrKey}/remotelink
Create or update remote issue link	Creates or updates a remote issue link for a specific issue. If a `globalId` is given and a matching remote issue link is found, it is updated and any fields not included in the request are set to null. If no matching `globalId` is found, a new remote issue link is created.	POST /rest/api/3/issue/{issueIdOrKey}/remotelink
Delete remote issue link by global ID	Deletes the remote issue link from the issue using the link's global ID.	DELETE /rest/api/3/issue/{issueIdOrKey}/remotelink
Get remote issue link by ID	Returns a remote issue link for an issue.	GET /rest/api/3/issue/{issueIdOrKey}/remotelink/{linkId}
Update remote issue link by ID	Updates a remote issue link for an issue.	PUT /rest/api/3/issue/{issueIdOrKey}/remotelink/{linkId}
Delete remote issue link by ID	Deletes a remote issue link from an issue.	DELETE /rest/api/3/issue/{issueIdOrKey}/remotelink/{linkId}

Issue search (version 2)

Name	Description	API docs link
Get issue suggestions	Retrieves lists of issues that match a given query string. It is used to offer auto-completion suggestions when searching for an issue matching a query string.	GET /rest/api/2/issue/picker
Check issues against JQL	Checks if one or more provided issues would be returned by one or more provided JQL queries.	POST /rest/api/2/jql/match
Search for issues using JQL (GET)	Searches for issues using JQL, using a short search term.	GET /rest/api/2/search
Search for issues using JQL (POST)	Searches for issues using JQL using a short or long search term.	POST /rest/api/2/search

Issue search (version 3)

Name	Description	API docs link
Get issue suggestions	Retrieves lists of issues that match a given query string. It is used to offer auto-completion suggestions when searching for an issue matching a query string.	GET /rest/api/3/issue/picker
Check issues against JQL	Checks if one or more provided issues would be returned by one or more provided JQL queries.	POST /rest/api/3/jql/match
Search for issues using JQL (GET)	Searches for issues using JQL, using a short search term.	GET /rest/api/3/search
Search for issues using JQL (POST)	Searches for issues using JQL using a short or long search term.	POST /rest/api/3/search

Issue votes (version 2)

Name	Description	API docs link
Delete vote	Deletes a user's vote from an issue, similar to the user clicking *Unvote* on an issue in Jira.	DELETE /rest/api/2/issue/{issueIdOrKey}/votes
Get votes	Returns details about the votes on an issue.	GET /rest/api/2/issue/{issueIdOrKey}/votes
Add vote	Adds the user's vote to an issue, similar to the user clicking *Vote* on an issue in Jira.	POST /rest/api/2/issue/{issueIdOrKey}/votes

Issue votes (version 3)

Name	Description	API docs link
Get votes	Returns details about the votes on an issue.	GET /rest/api/3/issue/{issueIdOrKey}/votes
Add vote	Adds the user's vote to an issue, similar to the user clicking *Vote* on an issue in Jira.	POST /rest/api/3/issue/{issueIdOrKey}/votes
Delete vote	Deletes a user's vote from an issue, similar to the user clicking *Unvote* on an issue in Jira.	DELETE /rest/api/3/issue/{issueIdOrKey}/votes

Issue watchers (version 2)

Name	Description	API docs link
------	-------------	---------------

Delete watcher	Deletes a user as a watcher of an issue.	DELETE /rest/api/2/issue/{issueIdOrKey}/watchers
Get issue watchers	Returns the watchers for an issue.	GET /rest/api/2/issue/{issueIdOrKey}/watchers
Add watcher	Adds a user as a watcher of an issue by passing the account ID of the user.	POST /rest/api/2/issue/{issueIdOrKey}/watchers

Issue watchers (version 3)

Name	Description	API docs link
Get issue watchers	Returns the watchers for an issue.	GET /rest/api/3/issue/{issueIdOrKey}/watchers
Add watcher	Adds a user as a watcher of an issue by passing the account ID of the user.	POST /rest/api/3/issue/{issueIdOrKey}/watchers
Delete watcher	Deletes a user as a watcher of an issue.	DELETE /rest/api/3/issue/{issueIdOrKey}/watchers

Issue worklog properties (version 2)

Name	Description	API docs link
Get worklog property keys	Returns the keys of all properties for a worklog.	GET /rest/api/2/issue/{issueIdOrKey}/worklog/{worklogId}/properties

Issue worklog properties (version 3)

Name	Description	API docs link
Get worklog property keys	Returns the keys of all properties for a worklog.	GET /rest/api/3/issue/{issueIdOrKey}/worklog/{worklogId}/properties

Issue worklogs (version 2)

Name	Description	API docs link
Get issue worklogs	Returns worklogs for a specific issue, either from the oldest worklog or from those started on or after a specified date and time.	GET /rest/api/2/issue/{issueIdOrKey}/worklog
Add worklog	Adds a worklog to an issue.	POST /rest/api/2/issue/{issueIdOrKey}/worklog
Delete worklog	Deletes a worklog from an issue.	DELETE /rest/api/2/issue/{issueIdOrKey}/worklog/{id}

Get worklog	Returns a worklog.	GET /rest/api/2/issue/{issueIdOrKey}/worklog/{id}
Update worklog	Updates a worklog.	PUT /rest/api/2/issue/{issueIdOrKey}/worklog/{id}
Get worklogs	Returns the details of worklogs from IDs, with field such as comment, updateAuthor, datestamps and timespent.	POST /rest/api/2/worklog/list
Get IDs of updated worklogs	Returns a list of details for worklogs updated since a particular time.	GET /rest/api/2/worklog/updated

Issue worklogs (version 3)

Name	Description	API docs link
Get issue worklogs	Returns worklogs for a specific issue, either from the oldest worklog or from those started on or after a specified date and time.	GET /rest/api/3/issue/{issueIdOrKey}/worklog
Add worklog	Adds a worklog to an issue.	POST /rest/api/3/issue/{issueIdOrKey}/worklog
Get worklog	Returns a worklog.	GET /rest/api/3/issue/{issueIdOrKey}/worklog/{id}
Update worklog	Updates a worklog.	PUT /rest/api/3/issue/{issueIdOrKey}/worklog/{id}
Delete worklog	Deletes a worklog from an issue.	DELETE /rest/api/3/issue/{issueIdOrKey}/worklog/{id}
Get worklogs	Returns the details of worklogs from IDs, with field such as comment, updateAuthor, datestamps and timespent.	POST /rest/api/3/worklog/list
Get IDs of updated worklogs	Returns a list of details for worklogs updated since a particular time.	GET /rest/api/3/worklog/updated

Issues (version 2)

Name	Description	API docs link
Create issue	Creates issue or a subtask with optional transition and properties.	POST /rest/api/2/issue
Archives issues by JQL	Archives up to 100,000 issues via JQL and returns status URL.	POST /rest/api/2/issue/archive
Archives issues by ID/key	Archives up to 1000 issues using ID/key and returns the details of the issues and any errors encountered.	PUT /rest/api/2/issue/archive

Create bulk issues or subtasks	Creates up to 50 issues and/or subtasks with optional transitions and properties.	POST /rest/api/2/issue/bulk
Get metadata for "create issue"	Returns metadata details of the create screen fields based on projects and issue types for the user.	GET /rest/api/2/issue/createmeta
Get create metadata issue types for project	Returns the create metadata for issue types in a project.	GET /rest/api/2/issue/createmeta/{projectIdOrKey}/issuetypes
Get create field metadata for a project and issue type	Get create metadata for a particular issue type in a project.	GET /rest/api/2/issue/createmeta/{projectIdOrKey}/issuetypes/{issueTypeId}
Unarchive issues by ID/key	Unarchives up to 1000 issues using ID/key and returns the details of the issues and any errors encountered.	PUT /rest/api/2/issue/unarchive
Delete issue	Deletes an issue.	DELETE /rest/api/2/issue/{issueIdOrKey}
Get issue	Returns the details for an issue by its ID or key.	GET /rest/api/2/issue/{issueIdOrKey}
Edit issue	Edits an issue. The issue's transition and/or properties may be changed.	PUT /rest/api/2/issue/{issueIdOrKey}
Assign issue	Assigns an issue to a user. Use this when the calling user does not have the *Edit Issues* permission but has the *Assign Issue* permission for the project that the issue is in.	PUT /rest/api/2/issue/{issueIdOrKey}/assignee
Get changelogs for an issue	Returns a paginated list of all changelogs for an issue sorted by descending date.	GET /rest/api/2/issue/{issueIdOrKey}/changelog
Get changelogs by IDs	Returns changelogs for an issue specified by a list of changelog IDs.	POST /rest/api/2/issue/{issueIdOrKey}/changelog/list
Get "edit issue" metadata	Returns metadata details of the edit screen fields based on an issue visible and editable to the user.	GET /rest/api/2/issue/{issueIdOrKey}/editmeta
Send email notification for an issue	Creates and sends an email notification for an issue.	POST /rest/api/2/issue/{issueIdOrKey}/notify
Get transitions	Returns all transitions, or a specific transition, that a user can perform on an issue, based on the current status of the issue.	GET /rest/api/2/issue/{issueIdOrKey}/transitions

Transition issue	Performs a transition on an issue and, if the transition has a screen, it updates the fields displayed on that transition screen.	POST /rest/api/2/issue/{issueIdOrKey}/transitions
Export archived issue(s)	Enables users to retrieve details of all archived issues.	PUT /rest/api/2/issues/archive/export

Issues (version 3)

Name	Description	API docs link
Create issue	Creates issue or a subtask with optional transition and properties.	POST /rest/api/3/issue
Archives issues by ID/key	Archives up to 1000 issues using ID/key and returns the details of the issues and any errors encountered.	PUT /rest/api/3/issue/archive
Archives issues by JQL	Archives up to 100,000 issues via JQL and returns status URL.	POST /rest/api/3/issue/archive
Create bulk issues or subtasks	Creates up to 50 issues and/or subtasks with optional transitions and properties.	POST /rest/api/3/issue/bulk
Get metadata for "create issue"	Returns metadata details of the create screen fields based on projects and issue types for the user.	GET /rest/api/3/issue/createmeta
Unarchive issues by ID/key	Unarchives up to 1000 issues using ID/key and returns the details of the issues and any errors encountered.	PUT /rest/api/3/issue/unarchive
Get issue	Returns the details for an issue by its ID or key.	GET /rest/api/3/issue/{issueIdOrKey}
Edit issue	Edits an issue. The issue's transition and/or properties may be changed.	PUT /rest/api/3/issue/{issueIdOrKey}
Delete issue	Deletes an issue.	DELETE /rest/api/3/issue/{issueIdOrKey}
Assign issue	Assigns an issue to a user. Use this when the calling user does not have the *Edit Issues* permission but has the *Assign Issue* permission for the project that the issue is in.	PUT /rest/api/3/issue/{issueIdOrKey}/assignee
Get changelogs for an issue	Returns a paginated list of all changelogs for an issue sorted by descending date.	GET /rest/api/3/issue/{issueIdOrKey}/changelog

Get changelogs by IDs	Returns changelogs for an issue specified by a list of changelog IDs.	POST /rest/api/3/issue/{issueIdOrKey}/changelog/list
Get "edit issue" metadata	Returns metadata details of the edit screen fields based on an issue visible and editable to the user.	GET /rest/api/3/issue/{issueIdOrKey}/editmeta
Send email notification for an issue	Creates and sends an email notification for an issue.	POST /rest/api/3/issue/{issueIdOrKey}/notify
Get transitions	Returns all transitions, or a specific transition, that a user can perform on an issue, based on the current status of the issue.	GET /rest/api/3/issue/{issueIdOrKey}/transitions
Transition issue	Performs a transition on an issue and, if the transition has a screen, it updates the fields displayed on that transition screen.	POST /rest/api/3/issue/{issueIdOrKey}/transitions
Export archived issue(s)	Enables users to retrieve details of all archived issues.	PUT /rest/api/3/issues/archive/export
Get create metadata issue types for project	Returns the create metadata for issue types in a project.	GET /rest/api/3/issue/createmeta/{projectIdOrKey}/issuetypes
Get create field metadata for a project and issue type	Get create metadata for a particular issue type in a project.	GET /rest/api/3/issue/createmeta/{projectIdOrKey}/issuetypes/{issueTypeId}

Jira expressions (version 2)

Name	Description	API docs link
Return Jira expression results	Returns a Jira expression's resulting values.	POST /rest/api/2/expression/eval

Jira expressions (version 3)

Name	Description	API docs link
Return Jira expression results	Returns a Jira expression's resulting values.	POST /rest/api/3/expression/eval

JQL (version 2)

Name	Description	API docs link
Get field autocomplete suggestions	Returns JQL search autocomplete suggestions for the provided field.	GET /rest/api/2/jql/autocomplete/data/suggestions
Parse JQL query	Checks whether the input is valid JQL.	POST /rest/api/2/jql/parse
Sanitize JQL queries	Converts human-readable details like project keys into IDs in the provided JQL query.	POST /rest/api/2/jql/sanitize

JQL (version 3)

Name	Description	API docs link
Get field autocomplete suggestions	Returns JQL search autocomplete suggestions for the provided field.	GET /rest/api/3/jql/autocomplete/data/suggestions
Parse JQL query	Checks whether the input is valid JQL.	POST /rest/api/3/jql/parse
Sanitize JQL queries	Converts human-readable details like project keys into IDs in the provided JQL query.	POST /rest/api/3/jql/sanitize

Labels (version 2)

Name	Description	API docs link
Get all labels	Returns all labels.	GET /rest/api/2/label

Labels (version 3)

Name	Description	API docs link
Get all labels	Returns all labels.	GET /rest/api/3/label

Permissions (version 2)

Name	Description	API docs link
Get my permissions	Returns all of the provided user's permissions.	GET /rest/api/2/mypermissions

Get permission grants	Returns a list of global and project permissions of the provided user.	POST /rest/api/2/permissions/check
-----------------------	--	------------------------------------

Permissions (version 3)

Name	Description	API docs link
Get my permissions	Returns all of the provided user's permissions.	GET /rest/api/3/mypermissions
Get permission grants	Returns a list of global and project permissions of the provided user.	POST /rest/api/3/permissions/check

Project features (version 2)

Name	Description	API docs link
Get project features	Returns a list of a project's features.	GET /rest/api/2/project/{projectIdOrKey}/features
Set project feature state	Sets the state of a project feature.	PUT /rest/api/2/project/{projectIdOrKey}/features/{featureKey}

Project features (version 3)

Name	Description	API docs link
Get project features	Returns a list of a project's features.	GET /rest/api/3/project/{projectIdOrKey}/features
Set project feature state	Sets the state of a project feature.	PUT /rest/api/3/project/{projectIdOrKey}/features/{featureKey}

Project permission schemes (version 2)

Name	Description	API docs link
Get project issue security levels	Returns a list of all issue security levels which the provided user can access within the provided project.	GET /rest/api/2/project/{projectKeyOrId}/securitylevel

Project permission schemes (version 3)

Name	Description	API docs link
------	-------------	---------------

Get project issue security levels	Returns a list of all issue security levels which the provided user can access within the provided project.	GET /rest/api/3/project/{projectKeyOrId}/securitylevel
-----------------------------------	---	---

Project roles (version 2)

Name	Description	API docs link
Get project role details	Returns all project roles and their details.	GET /rest/api/2/project/{projectIdOrKey}/roledetails

Project roles (version 3)

Name	Description	API docs link
Get project role details	Returns all project roles and their details.	GET /rest/api/3/project/{projectIdOrKey}/roledetails

Project versions (version 2)

Name	Description	API docs link
Get project versions paginated	Returns a paginated list of all versions in a project.	GET /rest/api/2/project/{projectIdOrKey}/version
Delete a project version DEPRECATED	Deletes a project version.	DELETE /rest/api/2/version/{id}
Get a project version	Returns information about a specific version of a Jira project, such as the project ID, description, name, its start date and release date, the list of approvers, and whether the version has been archived.	GET /rest/api/2/version/{id}
Update a project version	Updates information about a specific version of a Jira project, such as the project description, name, and its start date and release dates.	PUT /rest/api/2/version/{id}
Merge project versions	Merges two project versions. The merge is performed by deleting the specified project versions and updating the fix version for any issues specifying the deleted version to a new fix version specified by the user.	PUT /rest/api/2/version/{id}/mergeto/{moveIssuesTo}

Delete and replace a project version	Deletes the specified project version. The user can also specify other fix version, affected version, and custom field version values that will be used to update any issues that specify this version in those fields.	POST /rest/api/2/version/{id}/removeAndSwap
Get a project version's unresolved issues count	Returns the number of issues and the number of unresolved issues for the project version.	GET /rest/api/2/version/{id}/unresolvedIssueCount

Project versions (version 3)

Name	Description	API docs link
Get project versions paginated	Returns a paginated list of all versions in a project.	GET /rest/api/3/project/{projectIdOrKey}/version
Get a project version	Returns information about a specific version of a Jira project, such as the project ID, description, name, its start date and release date, the list of approvers, and whether the version has been archived.	GET /rest/api/3/version/{id}
Update a project version	Updates information about a specific version of a Jira project, such as the project description, name, and its start date and release dates.	PUT /rest/api/3/version/{id}
Delete a project version DEPRECATED	Deletes a project version.	DELETE /rest/api/3/version/{id}
Merge project versions	Merges two project versions. The merge is performed by deleting the specified project versions and updating the fix version for any issues specifying the deleted version to a new fix version specified by the user.	PUT /rest/api/3/version/{id}/mergeto/{moveIssuesTo}
Delete and replace a project version	Deletes the specified project version. The user can also specify other fix version, affected version, and custom field version values that will be used to update any issues that specify this version in those fields.	POST /rest/api/3/version/{id}/removeAndSwap
Get a project version's unresolved issues count	Returns the number of issues and the number of unresolved issues for the project version.	GET /rest/api/3/version/{id}/unresolvedIssueCount

Projects (version 2)

Name	Description	API docs link
------	-------------	---------------

Get all projects for user DEPRECATED	Returns all projects visible to the provided user.	GET /rest/api/2/project
Create project	Creates a project based on the provided project type template.	POST /rest/api/2/project
Get recent projects	Returns up to the 20 projects most recently viewed by the provided user.	GET /rest/api/2/project/recent
Get projects paginated	Returns a paginated list of the projects visible to the provided user.	GET /rest/api/2/project/search
Delete project	Deletes a project.	DELETE /rest/api/2/project/{projectIdOrKey}
Get project	Returns a project's details.	GET /rest/api/2/project/{projectIdOrKey}
Update project	Updates a project's details.	PUT /rest/api/2/project/{projectIdOrKey}
Delete project asynchronously	Deletes a project asynchronously.	POST /rest/api/2/project/{projectIdOrKey}/delete

Projects (version 3)

Name	Description	API docs link
Get all projects for user DEPRECATED	Returns all projects visible to the provided user.	GET /rest/api/3/project
Create project	Creates a project based on the provided project type template.	POST /rest/api/3/project
Get recent projects	Returns up to the 20 projects most recently viewed by the provided user.	GET /rest/api/3/project/recent
Get projects paginated	Returns a paginated list of the projects visible to the provided user.	GET /rest/api/3/project/search
Get project	Returns a project's details.	GET /rest/api/3/project/{projectIdOrKey}
Update project	Updates a project's details.	PUT /rest/api/3/project/{projectIdOrKey}
Delete project	Deletes a project.	DELETE /rest/api/3/project/{projectIdOrKey}
Delete project asynchronously	Deletes a project asynchronously.	POST /rest/api/3/project/{projectIdOrKey}/delete

Screen tabs (version 2)

Name	Description	API docs link
------	-------------	---------------

Get tabs for multiple screens	Returns all tabs for the provided listed of screens.	GET /rest/api/2/screens/tabs
-------------------------------	--	------------------------------

Screen tabs (version 3)

Name	Description	API docs link
Get tabs for multiple screens	Returns all tabs for the provided listed of screens.	GET /rest/api/3/screens/tabs

User search (version 2)

Name	Description	API docs link
Find users assignable to issues	Returns a list of users that can be assigned to a new issue, updated issue, or issue experiencing a workflow transition.	GET /rest/api/2/user/assignable/search
Find users with permissions	Returns a list of users that have the specified permissions for a project or issue.	GET /rest/api/2/user/permission/search
Find users by query	Returns a list of active users that match the specified search criteria related to their Jira activity. For example, you can list users who are assignees, reporters, watchers, voters, or commenters on specific issues. The returned list contains user details such as name, the groups the user belongs to, their avatar, and email address.	GET /rest/api/2/user/search/query
Find users with browse permission	Returns a list of users who can browse a specific issue or any issue in a specific project. The returned list can optionally be limited to users with profile attributes that match a search term.	GET /rest/api/2/user/viewissue/search

User search (version 3)

Name	Description	API docs link
Find users assignable to issues	Returns a list of users that can be assigned to a new issue, updated issue, or issue experiencing a workflow transition.	GET /rest/api/3/user/assignable/search
Find users with permissions	Returns a list of users that have the specified permissions for a project or issue.	GET /rest/api/3/user/permission/search

Find users by query	Returns a list of active users that match the specified search criteria related to their Jira activity. For example, you can list users who are assignees, reporters, watchers, voters, or commenters on specific issues. The returned list contains user details such as name, the groups the user belongs to, their avatar, and email address.	GET /rest/api/3/user/search/query
Find users with browse permission	Returns a list of users who can browse a specific issue or any issue in a specific project. The returned list can optionally be limited to users with profile attributes that match a search term.	GET /rest/api/3/user/viewissue/search

Jira Software

These APIs are only used by software projects.

Backlog

Name	Description	API docs link
Moves issues to a board's backlog	Moves issues from an existing board to the board's backlog.	POST /rest/agile/backlog/{boardId}/issue
Moves issues to a backlog	Moves issues to the backlog.	POST /rest/agile/backlog/issue

Board

Name	Description	API docs link
Get issues from a backlog	Returns all issues from the board's backlog.	GET /rest/agile/board/{boardId}/backlog
Get details for epics	Returns all epics from the board.	GET /rest/agile/board/{boardId}/epic
Get issues for board	Returns all issues for a board.	GET /rest/agile/board/{boardId}/issue
Get all sprints	Returns all sprints for a board.	GET /rest/agile/board/{boardId}/sprint
Get the board issues for a sprint	Gets all issues that belong to a sprint.	GET /rest/agile/board/{boardId}/sprint/{sprintId}/issue
Toggle features	Turn features on or off.	PUT /rest/agile/board/{boardId}/features
Delete a board	Deletes a board.	DELETE /rest/agile/board/{boardId}
Get board details	Returns a board based on ID, if the user has permission.	GET /rest/agile/board

Get board configuration	Gets details of the board configuration.	GET /rest/agile/board/{boardId}
Get board issues for epic	Returns issues belonging to an epic.	GET /rest/agile/board/{boardId}/configuration
Get issues without epic for board	Returns all issues on a board that don't belong to an epic.	GET /rest/agile/board/{boardId}/epic/{epicId}/issue
Get features for board	Returns the features on a board.	GET /rest/agile/board/{boardId}/epic/none/issue
Get projects based on board	Returns all projects that are associated with a board.	GET /rest/agile/board/{boardId}/features
Get associated projects to board	Returns all projects that are statically associated with a board.	GET /rest/agile/board/{boardId}/project
Get keys for a board property	Returns the keys of all properties for a board.	GET /rest/agile/board/{boardId}/project/full
Get all quick filters	Returns all quick filters for a board.	GET /rest/agile/board/{boardId}/properties
Get details of quick filter	Returns the quick filter details.	GET /rest/agile/board/{boardId}/quickfilter
Get reports for board	Returns the reports for a board.	GET /rest/agile/board/{boardId}/quickfilter/{quickFilterId}
Get all versions	Gets all versions for a board.	GET /rest/agile/board/{boardId}/reports
Create a board	Creates a new board.	GET /rest/agile/board/{boardId}/version
Move issues to board	Moves issue from the backlog to the board.	POST /rest/agile/board
Get all boards	Returns all boards that the user has permission to view.	POST /rest/agile/board/{boardId}/issue

Builds

Name	Description	API docs link
Add or update build data	Adds or updates data for the specified build, such as the build label, related Jira issue keys, the build status, and related commits and branches.	POST /rest/builds/bulk
Bulk delete builds by property	Bulk removes all build data that matches all of the specified properties.	DELETE /rest/builds/bulkByProperties
Get information for a build	Returns data for the specified build.	GET /rest/builds/pipelines/{pipelineId}/builds/{buildNumber}
Delete information for a build	Removes build data for the specified build.	DELETE /rest/builds/pipelines/{pipelineId}/builds/{buildNumber}

Deployments

Name	Description	API docs link
Add or update deployment data	Adds or updates data related to a specific deployment which may be associated with one or more Jira issue keys and other properties in the request.	POST /rest/deployments/bulk
Bulk delete deployment information from Jira Software by property	Bulk removes deployment information that matches all of the specified properties.	DELETE /rest/deployments/bulkByProperties
Get deployment by key	Returns the current deployment data for the deployment that matches the specified properties.	GET /rest/deployments/pipelines/{pipelineId}/environments/{environmentId}/deployments/{deploymentSequenceNumber}
Delete deployment by key	Removes the current deployment data for the deployment that matches the specified properties.	DELETE /rest/deployments/pipelines/{pipelineId}/environments/{environmentId}/deployments/{deploymentSequenceNumber}
Get deployment check status for a deployment by key	Returns information about the progress of the specified deployment through deployment checks. A deployment may be allowed, prevented, awaiting, or invalid.	GET /rest/deployments/pipelines/{pipelineId}/environments/{environmentId}/deployments/{deploymentSequenceNumber}/gating-status

Deployment information

Name	Description	API docs link
Add or update development information for this installation, to make it available for use and display in Jira.	Adds or updates development information such as code commits, pull (code modification) requests and version branches for one or more repositories.	POST /rest/devinfo/bulk
Get development information	Returns development information for the specified repository, including recent commits, branches, and pull requests.	GET /rest/devinfo/repository/{repositoryId}
Delete development information	Removes development information for the specified repository from Jira Software, including the list of all commits, pull requests, and branches associated with it.	DELETE /rest/devinfo/repository/{repositoryId}
Delete development information by properties	Removes development information whose properties match the values of all of the specified properties.	DELETE /rest/devinfo/bulkByProperties

Check existence of development information matching supplied properties	Checks for existence of development information matching all of the supplied properties.	GET /rest/devinfo/existsByProperties
Delete development information	Removes development information matching the provided repository, information type (commit, branch or pull request), and entity ID.	DELETE /rest/devinfo/repository/{repositoryId}/{entityType}/{entityId}

Epic

Name	Description	API docs link
Get the details for an epic	Returns the epic details.	GET /rest/agile/epic/{epicIdOrKey}
Get issues for an epic	Returns all the issues for an epic.	GET /rest/agile/epic/{epicIdOrKey}/issue
Reorder epics	Moves an epic before or after another epic.	PUT /rest/agile/epic/{epicIdOrKey}/rank
Partially update an epic	Updates part of the epic	POST /rest/agile/epic/{epicIdOrKey}
Move issues to an epic	Moves issues to an epic.	POST /rest/agile/epic/{epicIdOrKey}/issue
Remove issues from an epic	Removes issues from epics.	POST /rest/agile/epic/none/issue

Feature flags

Name	Description	API docs link
Add or update feature flag information	Adds or updates information for one or more feature flags. Feature flag data can only be accessed by certain types of apps.	POST /rest/featureflags/bulk
Bulk delete feature flag data by property	Removes information for feature flags that match all of the specified properties.	DELETE /rest/featureflags/bulkByProperties
Get data for a feature flag	Returns feature flag information for the specified feature flag.	GET /rest/featureflags/flag/{featureFlagId}
Delete data for a feature flag	Removes information for the specified feature flag.	DELETE /rest/featureflags/flag/{featureFlagId}

Issue

Name	Description	API docs link
Get details for an issue	Returns the details of an issue.	GET /rest/agile/issue/{issueIdOrKey}
Reorder issues	Moves issues before or after another issue.	PUT /rest/agile/issue/rank
Get issue estimation for board	Returns the field and the value for an estimation for a board.	GET /rest/agile/issue/{issueIdOrKey}/estimation
Estimate issue for board	Updates the estimation of the issue.	PUT /rest/agile/issue/{issueIdOrKey}/estimation

Remote links

Name	Description	API docs link
Add or update remote link data	Adds or updates remote link data, such as the provider's URL, a list of actions that can be performed by Jira users on the remote link, and a documentation URL for the remote link.	POST /rest/remotelinks/bulk
Bulk delete remote links by property	Bulk removes remote links that match all of the specified properties.	DELETE /rest/remotelinks/bulkByProperties
Get remote link data	Returns data for the remote link identified by the specified remote link ID.	GET /rest/remotelinks/remotelink/{remoteLinkId}
Delete remote link	Removes the specified remote link.	DELETE /rest/remotelinks/remotelink/{remoteLinkId}

Security information

Name	Description	API docs link
Add security workspace IDs to this Jira site	Adds security workspace IDs to establish a relationship between them and the Jira site the app is installed on.	POST /rest/security/linkedWorkspaces/bulk
Bulk delete linked security workspaces	Bulk removes the links to the specified security workspaces.	DELETE /rest/security/linkedWorkspaces/bulk
Get linked security workspaces	Returns a list of all security workspaces linked to the Jira site.	GET /rest/security/linkedWorkspaces
Get linked security workspace by ID	Returns data for the specified security workspace, such as the last date and time it was updated in Jira.	GET /rest/security/linkedWorkspaces/{workspaceId}

Add or update vulnerability data	Adds or updates vulnerability data, such as the severity, status, date introduced, and summary URL for a vulnerability.	POST /rest/security/bulk
Bulk delete vulnerabilities by property	Bulk removes vulnerabilities matching all of the specified properties.	DELETE /rest/security/bulkByProperties
Get data for a vulnerability	Returns data for the specified vulnerability.	GET /rest/security/vulnerability/{vulnerabilityId}
Delete data for a vulnerability	Removes data for the specified vulnerability.	DELETE /rest/security/vulnerability/{vulnerabilityId}

Sprint

Name	Description	API docs link
Get issues for a sprint	Returns details of all issues in a sprint.	GET /rest/agile/sprint/{sprintId}/issue
Move issues to a sprint	Moves issues to a sprint.	POST /rest/agile/sprint/{sprintId}/issue
Delete a sprint	Deletes a sprint.	DELETE /rest/agile/sprint/{sprintId}
Get details for a sprint	Returns the details of a sprint.	GET /rest/agile/sprint/{sprintId}
Create a sprint	Creates a future sprint.	POST /rest/agile/sprint
Swap a sprint position	Swaps the position of a sprint with another sprint.	POST /rest/agile/sprint/{sprintId}/swap

Jira Service Management

These APIs are only used by service management projects.

Organization

Name	Description	API docs link
Remove organization from service desk	Removes an organization by ID from a service desk.	DELETE /rest/servicedeskapi/servicedesk/{serviceDeskId}/organization
Get organizations associated with service desk	Returns the details of all the organizations associated with a service desk.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/organization

Add organization to service desk	Adds an organization by ID to a service desk.	POST /rest/servicedeskapi/servicedesk/{serviceDeskId}/organization
----------------------------------	---	---

Request

Name	Description	API docs link
Unsubscribe from a request	Unsubscribes the current user from a request.	DELETE /rest/servicedeskapi/request/{issuelIdOrKey}/notification
Remove participants from a request	Removes one or more participants from a request.	DELETE /rest/servicedeskapi/request/{issuelIdOrKey}/participant
Delete feedback for request	Deletes feedback associated with a request.	DELETE /rest/servicedeskapi/request/{requestIdOrKey}/feedback
Get my requests	Returns all customer requests for the current user.	GET /rest/servicedeskapi/request
Get a request by ID or key	Returns the details of a customer request by ID of Key	GET /rest/servicedeskapi/request/{issuelIdOrKey}
Get approvals for request	Returns all the details of the approvals for a request.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/approval
Get details of approval	Returns the details of a specific approval.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/approval/{approvalId}
Get attachments for a request	Returns details of all attachments on a customer request.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/attachment
Get attachment	Returns the contents of an attachment.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/attachment/{attachmentId}
Get attachment thumbnail	Returns the thumbnail of the attachment.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/attachment/{attachmentId}/thumbnail
Get comments on request	Returns all the comments on a request.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/comment
Get a comment	Returns all the details about a specific comment.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/comment/{commentId}
Get attachments on comment	Returns all the attachments associated with a comment.	GET /rest/servicedeskapi/request/{issuelIdOrKey}/comment/{commentId}/attachment

Get my subscription status for a request	Returns the notification subscription status of the current user for a request.	GET /rest/servicedeskapi/request/{issueIdOrKey}/notification
Get list of request participants	Returns a list of all the participants of a request.	GET /rest/servicedeskapi/request/{issueIdOrKey}/participant
Get SLA details for request	Returns all the SLA details on a request, such as start time, breach time, and the SLA goals.	GET /rest/servicedeskapi/request/{issueIdOrKey}/sla
Get SLA details	Returns the details for a specific SLA on a customer request.	GET /rest/servicedeskapi/request/{issueIdOrKey}/sla/{slaMetricId}
Get request status and history	Returns a list of all the existing and current statuses a request has been in.	GET /rest/servicedeskapi/request/{issueIdOrKey}/status
Get transitions	Returns a list of the workflow processes that move a request through statuses (transitions) that the user can perform on a request.	GET /rest/servicedeskapi/request/{issueIdOrKey}/transition
Get feedback for request	Returns a feedback of a request, including rating and comments.	GET /rest/servicedeskapi/request/{requestIdOrKey}/feedback
Create a request	Creates a customer request in a service desk.	POST /rest/servicedeskapi/request
Answer approval	Approves or declines an approval on a request.	POST /rest/servicedeskapi/request/{issueIdOrKey}/approval/{approvalId}
Create an attachment	Creates an attachment (and an optional comment) as a temporary file attached to a request.	POST /rest/servicedeskapi/request/{issueIdOrKey}/attachment
Create a comment on request	Creates a public or private comment on an existing request.	POST /rest/servicedeskapi/request/{issueIdOrKey}/comment
Add participants to a request	Adds one or more participants to a request.	POST /rest/servicedeskapi/request/{issueIdOrKey}/participant
Make a transition	Makes a transition for a given request, with an optional comment.	POST /rest/servicedeskapi/request/{issueIdOrKey}/transition
Add feedback to request	Adds feedback to a request.	POST /rest/servicedeskapi/request/{requestIdOrKey}/feedback
Subscribe to a request	Subscribes the current user to a request.	PUT /rest/servicedeskapi/request/{issueIdOrKey}/notification

Request type

Name	Description	API docs link
Get all request types	Returns all request types in a Jira Service Management instance.	GET /rest/servicedeskapi/requesttype
Delete a request type	Deletes a customer request type from a service desk, and removes it from all customer requests.	DELETE /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}

Service desk

Name	Description	API docs link
Get details of queue	Returns the details of a specific queue, with details such the queue name, JQL, fields, issueCount.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/queue/{queueId}
Get issues in a queue	Returns the details of the customer requests in a given queue. Lists only the fields the queue is configured to show.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/queue/{queueId}/issue
Get request types from a service desk	Returns the details of all the request types from a service desk, such as name, description, help desk, IDs etc.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype
Get request type by ID	Returns the details of a request type. Includes details such as name, description, IDs, icons.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}
Get fields for request type	Returns the fields for a service desk's request type. Examples include fieldID, name, requires, visibility etc.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}/field
Create a request type	Adds a customer request types to a service desk.	POST /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype
Remove customers from service desk	Removes one or more customers to a service desk, based on accountIds.	DELETE /rest/servicedeskapi/servicedesk/{serviceDeskId}/customer
Get service desk by ID	Returns details for a service desk, such as Project name, Key, ID.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}

Get list of customers for a service desk	Gets a list of all the details of customers for a service desk, such as ID, name, key, email, timezone etc.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/customer
Get queues in a service desk	Returns the details of the queues in a service desk, with details such as the queue name, JQL, fields, issueCount.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/queue
Get keys of all properties by request type	Returns the keys for all the properties based on a type of request.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}/property
Get groups of request types	Returns the service desk's request type groups.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttypegroup
Attach a temporary file to service desk	Adds one or more temporary attachments to a service desk.	POST /rest/servicedeskapi/servicedesk/{serviceDeskId}/attachTemporaryFile
Add customers to service desk	Adds one or more customers to a service desk, based on account IDs.	POST /rest/servicedeskapi/servicedesk/{serviceDeskId}/customer

Not blocked when an app access rule applies

These APIs are not blocked when the admin turns on an app access rule. This means that apps can still use these APIs to access Jira projects and content even when the admin has decided to block app access.

Jira Platform

These APIs are used by all Jira products.

Announcement banner (version 2)

Name	Description	API docs link
Get announcement banner configuration	Returns the current announcement banner configuration.	GET /rest/api/2/announcementBanner
Update announcement banner configuration	Updates the current announcement banner configuration.	PUT /rest/api/2/announcementBanner

Announcement banner (version 3)

Name	Description	API docs link
Get announcement banner configuration	Returns the current announcement banner configuration.	GET /rest/api/3/announcementBanner
Update announcement banner configuration	Updates the current announcement banner configuration.	PUT /rest/api/3/announcementBanner

Application roles (version 2)

Name	Description	API docs link
Get all application roles	Returns a list of application roles.	GET /rest/api/2/applicationrole
Get application role	Returns an application role	GET /rest/api/2/applicationrole/{key}
Get audit records	Returns a list of audit records.	GET /rest/api/2/auditing/record

Application roles (version 3)

Name	Description	API docs link
Get all application roles	Returns a list of application roles.	GET /rest/api/3/applicationrole
Get application role	Returns an application role	GET /rest/api/3/applicationrole/{key}
Get audit records	Returns a list of audit records.	GET /rest/api/3/auditing/record

Avatars (version 2)

Name	Description	API docs link
Get system avatars by type	Returns a list of system avatar details by owner type (where owner types are issue type, project, or user). This operation can be accessed anonymously.	GET /rest/api/2/avatar/{type}/system
Delete an avatar	Deletes an avatar for a project or issue type.	DELETE /rest/api/2/universal_avatar/type/{type}/owner/{owningObjectId}/avatar/{id}
Get avatar image by type	Returns the default project or issue type avatar image.	GET /rest/api/2/universal_avatar/view/type/{type}

Get an avatar image by owner	Returns the avatar image for a project or issue type.	GET /rest/api/2/universal_avatar/view/type/{type}/owner/{entityId}
------------------------------	---	--

Avatars (version 3)

Name	Description	API docs link
Get system avatars by type	Returns a list of system avatar details by owner type (where owner types are issue type, project, or user). This operation can be accessed anonymously.	GET /rest/api/3/avatar/{type}/system
Delete an avatar	Deletes an avatar for a project or issue type.	DELETE /rest/api/3/universal_avatar/type/{type}/owner/{owningObjectId}/avatar/{id}
Get avatar image by type	Returns the default project or issue type avatar image.	GET /rest/api/3/universal_avatar/view/type/{type}
Get an avatar image by owner	Returns the avatar image for a project or issue type.	GET /rest/api/3/universal_avatar/view/type/{type}/owner/{entityId}

Dashboards (version 2)

Name	Description	API docs link
Get all of a user's dashboards	Returns a list of all dashboards owned by or shared with the user. This option can be accessed anonymously.	GET /rest/api/2/dashboard
Create a new dashboard	Creates a new dashboard.	POST /rest/api/2/dashboard
Bulk edit dashboards	Apply identical changes across multiple dashboards.	PUT /rest/api/2/dashboard/bulk/edit
Get all available dashboard gadgets	List all available gadgets that can be added to all dashboards.	GET /rest/api/2/dashboard/gadgets
Get all dashboards by attribute	Returns a list of dashboards that match a specific attribute (for example, name).	GET /rest/api/2/dashboard/search

Get all gadgets from a dashboard	Returns a list of gadgets on a dashboard.	GET /rest/api/2/dashboard/{dashboardId}/gadget
Add dashboard gadget	Adds a gadget to a dashboard.	POST /rest/api/2/dashboard/{dashboardId}/gadget
Remove dashboard gadget	Removes a dashboard from a dashboard.	DELETE /rest/api/2/dashboard/{dashboardId}/gadget/{gadgetId}
Update dashboard gadget	Changes the title, position, or color of a gadget on a dashboard.	PUT /rest/api/2/dashboard/{dashboardId}/gadget/{gadgetId}
Get dashboard item property keys	Returns the keys of all the properties of a dashboard item. This operation can be accessed anonymously.	GET /rest/api/2/dashboard/{dashboardId}/items/{itemId}/properties
Delete dashboard item property	Deletes a dashboard item property. This operation can be accessed anonymously.	DELETE /rest/api/2/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Get dashboard item property	Returns the key and value of a dashboard item property.	GET /rest/api/2/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Set dashboard item property	Sets the value of a dashboard item property (used in apps to store custom data against a dashboard item).	PUT /rest/api/2/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Delete dashboard	Deletes a dashboard owned by the user.	DELETE /rest/api/2/dashboard/{id}
Get dashboard	Returns a dashboard. This operation can be accessed anonymously.	GET /rest/api/2/dashboard/{id}
Update dashboard	Updates a dashboard owned by the user. This operation can be accessed anonymously.	PUT /rest/api/2/dashboard/{id}
Copy dashboard	Copies a dashboard owned by the user.	POST /rest/api/2/dashboard/{id}/copy

Dashboards (version 3)

Name	Description	API docs link
Get all of a user's dashboards	Returns a list of all dashboards owned by or shared with the user. This option can be accessed anonymously.	GET /rest/api/3/dashboard

Create a new dashboard	Creates a new dashboard.	POST /rest/api/3/dashboard
Bulk edit dashboards	Apply identical changes across multiple dashboards.	PUT /rest/api/3/dashboard/bulk/edit
Get all available dashboard gadgets	List all available gadgets that can be added to all dashboards.	GET /rest/api/3/dashboard/gadgets
Get all dashboards by attribute	Returns a list of dashboards that match a specific attribute (for example, name).	GET /rest/api/3/dashboard/search
Get all gadgets from a dashboard	Returns a list of gadgets on a dashboard.	GET /rest/api/3/dashboard/{dashboardId}/gadget
Add dashboard gadget	Adds a gadget to a dashboard.	POST /rest/api/3/dashboard/{dashboardId}/gadget
Update dashboard gadget	Changes the title, position, or color of a gadget on a dashboard.	PUT /rest/api/3/dashboard/{dashboardId}/gadget/{gadgetId}
Remove dashboard gadget	Removes a dashboard from a dashboard.	DELETE /rest/api/3/dashboard/{dashboardId}/gadget/{gadgetId}
Get dashboard item property keys	Returns the keys of all the properties of a dashboard item. This operation can be accessed anonymously.	GET /rest/api/3/dashboard/{dashboardId}/items/{itemId}/properties
Get dashboard item property	Returns the key and value of a dashboard item property.	GET /rest/api/3/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Set dashboard item property	Sets the value of a dashboard item property (used in apps to store custom data against a dashboard item).	PUT /rest/api/3/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Delete dashboard item property	Deletes a dashboard item property. This operation can be accessed anonymously.	DELETE /rest/api/3/dashboard/{dashboardId}/items/{itemId}/properties/{propertyKey}
Get dashboard	Returns a dashboard. This operation can be accessed anonymously.	GET /rest/api/3/dashboard/{id}
Update dashboard	Updates a dashboard owned by the user. This operation can be accessed anonymously.	PUT /rest/api/3/dashboard/{id}
Delete dashboard	Deletes a dashboard owned by the user.	DELETE /rest/api/3/dashboard/{id}
Copy dashboard	Copies a dashboard owned by the user.	POST /rest/api/3/dashboard/{id}/copy

Filter sharing (version 2)

Name	Description	API docs link
Get the default share scope	Returns the default sharing settings for new filters and dashboards for a user.	GET /rest/api/2/filter/defaultShareScope
Set the default share scope	Sets the default sharing for new filters and dashboards for a user.	PUT /rest/api/2/filter/defaultShareScope

Filter sharing (version 3)

Name	Description	API docs link
Get the default share scope	Returns the default sharing settings for new filters and dashboards for a user.	GET /rest/api/3/filter/defaultShareScope
Set the default share scope	Sets the default sharing for new filters and dashboards for a user.	PUT /rest/api/3/filter/defaultShareScope

Filters (version 2)

Name	Description	API docs link
Get my favorite filter	Returns the visible favourite filters of the current user.	GET /rest/api/2/filter/favourite
Delete a filter	Deletes a filter, by ID.	DELETE /rest/api/2/filter/{id}
Get filter details	Returns all the details of a filter, including name, description, owner, JQL etc.	GET /rest/api/2/filter/{id}
Update a filter	Updates a filter, changing details such as name, description, JQL, or sharing permissions.	PUT /rest/api/2/filter/{id}

Filters (version 3)

Name	Description	API docs link
Get my favorite filter	Returns the visible favourite filters of the current user.	GET /rest/api/3/filter/favourite
Get filter details	Returns all the details of a filter, including name, description, owner, JQL etc.	GET /rest/api/3/filter/{id}
Update a filter	Updates a filter, changing details such as name, description, JQL, or sharing permissions.	PUT /rest/api/3/filter/{id}
Delete a filter	Deletes a filter, by ID.	DELETE /rest/api/3/filter/{id}

Group and user picker (version 2)

Name	Description	API docs link
Find users and groups.	Finds a list of users and groups.	GET /rest/api/2/groupuserpicker

Group and user picker (version 3)

Name	Description	API docs link
Find users and groups.	Finds a list of users and groups.	GET /rest/api/3/groupuserpicker

Groups (version 2)

Name	Description	API docs link
Delete group	Deletes a group.	DELETE /rest/api/2/group
Get group DEPRECATED	Returns all users in a group.	GET /rest/api/2/group
Create group	Creates a group.	POST /rest/api/2/group
Get groups	Gets a list of paginated groups.	GET /rest/api/2/group/bulk
Get users from a group	Gets a paginated list of users in a group.	GET /rest/api/2/group/member
Remove user from group	Removes a user from a group.	DELETE /rest/api/2/group/user
Add user to group	Adds a user to a group.	POST /rest/api/2/group/user
List groups	Lists sorted groups with matching queries. Returns empty if no match.	GET /rest/api/2/groups/picker

Groups (version 3)

Name	Description	API docs link
Get group DEPRECATED	Returns all users in a group.	GET /rest/api/3/group
Create group	Creates a group.	POST /rest/api/3/group

Delete group	Deletes a group.	DELETE /rest/api/3/group
Get groups	Gets a list of paginated groups.	GET /rest/api/3/group/bulk
Get users from a group	Gets a paginated list of users in a group.	GET /rest/api/3/group/member
Add user to group	Adds a user to a group.	POST /rest/api/3/group/user
Remove user from group	Removes a user from a group.	DELETE /rest/api/3/group/user
List groups	Lists sorted groups with matching queries. Returns empty if no match.	GET /rest/api/3/groups/picker

Issue attachments (version 2)

Name	Description	API docs link
Get Jira attachment settings	Returns the current Jira attachment settings (as in, whether attachments are enabled and the maximum attachment size allowed). This operation can be accessed anonymously.	GET /rest/api/2/attachment/meta

Issue attachments (version 3)

Name	Description	API docs link
Get attachment strings	Returns the current Jira attachment settings (as in, whether attachments are enabled and the maximum attachment size allowed). This operation can be accessed anonymously.	GET /rest/api/3/attachment/meta

Issue attachment properties (version 2)

Name	Description	API docs link
Delete comment property	Deletes a comment property.	DELETE /rest/api/2/comment/{commentId}/properties/{propertyKey}
Get comment property	Returns the value of a comment property. This operation can be accessed anonymously.	GET /rest/api/2/comment/{commentId}/properties/{propertyKey}
Set comment property	Sets or updates the value of a comment's property. Can be used to store custom data against a comment.	PUT /rest/api/2/comment/{commentId}/properties/{propertyKey}

Issue attachment properties (version 3)

Name	Description	API docs link
Get comment property	Returns the value of a comment property. This operation can be accessed anonymously.	GET /rest/api/3/comment/{commentId}/properties/{propertyKey}
Set comment property	Sets or updates the value of a comment's property. Can be used to store custom data against a comment.	PUT /rest/api/3/comment/{commentId}/properties/{propertyKey}
Delete comment property	Deletes a comment property.	DELETE /rest/api/3/comment/{commentId}/properties/{propertyKey}

Issue custom field configuration (apps) (version 2)

Name	Description	API docs link
Get configurations of app-owned custom fields	Returns a paginated list of configurations for a custom field created by the app.	GET /rest/api/2/app/field/{fieldIdOrKey}/context/configuration
Update configurations of app-owned custom fields	Updates the configuration for contexts of custom fields created by the app.	PUT /rest/api/2/app/field/{fieldIdOrKey}/context/configuration

Issue custom field configuration (apps) (version 3)

Name	Description	API docs link
Get configurations of app-owned custom fields	Returns a paginated list of configurations for a custom field created by the app.	GET /rest/api/3/app/field/{fieldIdOrKey}/context/configuration
Update configurations of app-owned custom fields	Updates the configuration for contexts of custom fields created by the app.	PUT /rest/api/3/app/field/{fieldIdOrKey}/context/configuration

Issue custom field contexts (version 2)

Name	Description	API docs link
Get custom field contexts	Returns a list of a custom field's contexts.	GET /rest/api/2/field/{fieldId}/context
Create custom field context	Creates a custom field context or a global context.	POST /rest/api/2/field/{fieldId}/context
Get custom field context defaults	Returns a list of default values for a custom field.	GET /rest/api/2/field/{fieldId}/context/defaultValue

Set custom field context default	Sets default values for custom field contexts.	PUT /rest/api/2/field/{fieldId}/context/defaultValue
Get issue types for custom field contexts	Returns a list of issue types used by each context of a custom field.	GET /rest/api/2/field/{fieldId}/context/issuetypemapping
Get issue and project types for each custom field context	Returns a list of issue types or project types used by each context of a custom field.	POST /rest/api/2/field/{fieldId}/context/mapping
Get project mappings for custom field context	Returns a list of projects mapped to each context of a custom field.	GET /rest/api/2/field/{fieldId}/context/projectmapping
Delete custom field context	Deletes a custom field's context.	DELETE /rest/api/2/field/{fieldId}/context/{contextId}
Update custom field context	Updates a custom field's context.	PUT /rest/api/2/field/{fieldId}/context/{contextId}
Add issue types to context	Adds issue types to a custom field context.	PUT /rest/api/2/field/{fieldId}/context/{contextId}/issuetype
Remove issue types from context	Removes issue types from a custom field context.	POST /rest/api/2/field/{fieldId}/context/{contextId}/issuetype/remove
Assign custom field context to a project	Assigns a custom field context to a project.	PUT /rest/api/2/field/{fieldId}/context/{contextId}/project
Remove custom field context from project	Removes a custom field context from a project.	POST /rest/api/2/field/{fieldId}/context/{contextId}/project/remove

Issue custom field contexts (version 3)

Name	Description	API docs link
Get custom field contexts	Returns a list of a custom field's contexts.	GET /rest/api/3/field/{fieldId}/context
Create custom field context	Creates a custom field context or a global context.	POST /rest/api/3/field/{fieldId}/context
Get custom field context defaults	Returns a list of default values for a custom field.	GET /rest/api/3/field/{fieldId}/context/defaultValue
Set custom field context default	Sets default values for custom field contexts.	PUT /rest/api/3/field/{fieldId}/context/defaultValue
Get issue types for custom field contexts	Returns a list of issue types used by each context of a custom field.	GET /rest/api/3/field/{fieldId}/context/issuetypemapping
Get issue and project types for each custom field context	Returns a list of issue types or project types used by each context of a custom field.	POST /rest/api/3/field/{fieldId}/context/mapping

Get project mappings for custom field context	Returns a list of projects mapped to each context of a custom field.	GET /rest/api/3/field/{fieldId}/context/projectmapping
Update custom field context	Updates a custom field's context.	PUT /rest/api/3/field/{fieldId}/context/{contextId}
Delete custom field context	Deletes a custom field's context.	DELETE /rest/api/3/field/{fieldId}/context/{contextId}
Add issue types to context	Adds issue types to a custom field context.	PUT /rest/api/3/field/{fieldId}/context/{contextId}/issuetype
Remove issue types from context	Removes issue types from a custom field context.	POST /rest/api/3/field/{fieldId}/context/{contextId}/issuetype/remove
Assign custom field context to a project	Assigns a custom field context to a project.	PUT /rest/api/3/field/{fieldId}/context/{contextId}/project
Remove custom field context from project	Removes a custom field context from a project.	POST /rest/api/3/field/{fieldId}/context/{contextId}/project/remove

Issue custom field options (version 2)

Name	Description	API docs link
Get an app-owned custom field selection option	Returns an option from a selection list of a custom field owned by the app. This operation can be accessed anonymously.	GET /rest/api/2/customFieldOption/{id}
Get custom field context options	Returns a list of all options for a custom field context.	GET /rest/api/2/field/{fieldId}/context/{contextId}/option
Create new custom field context options	Adds new options to a custom field context.	POST /rest/api/2/field/{fieldId}/context/{contextId}/option
Update custom field context options	Updates the options of a custom field context.	PUT /rest/api/2/field/{fieldId}/context/{contextId}/option
Reorder custom field context options	Changes the order of custom field context options.	PUT /rest/api/2/field/{fieldId}/context/{contextId}/option/move
Delete custom field context option	Deletes a custom field context option.	DELETE /rest/api/2/field/{fieldId}/context/{contextId}/option/{optionId}

Issue custom field options (version 3)

Name	Description	API docs link
Get an app-owned custom field selection option	Returns an option from a selection list of a custom field owned by the app. This operation can be accessed anonymously.	GET /rest/api/3/customFieldOption/{id}
Get custom field context options	Returns a list of all options for a custom field context.	GET /rest/api/3/field/{fieldId}/context/{contextId}/option
Update custom field context options	Updates the options of a custom field context.	PUT /rest/api/3/field/{fieldId}/context/{contextId}/option
Create new custom field context options	Adds new options to a custom field context.	POST /rest/api/3/field/{fieldId}/context/{contextId}/option
Reorder custom field context options	Changes the order of custom field context options.	PUT /rest/api/3/field/{fieldId}/context/{contextId}/option/move
Delete custom field context option	Deletes a custom field context option.	DELETE /rest/api/3/field/{fieldId}/context/{contextId}/option/{optionId}

Issue custom field options (apps) (version 2)

Name	Description	API docs link
Get all options for a issue field	Returns a list of all the options of a select list in an issue field	GET /rest/api/2/field/{fieldKey}/option
Create issue field option	Creates an option for a select list issue field.	POST /rest/api/2/field/{fieldKey}/option
Delete issue field option (added by app)	Deletes an option from a select list issue field, but only for fields added by Connect apps.	DELETE /rest/api/2/field/{fieldKey}/option/{optionId}
Get options for issue field	Returns the options from a select list issue field, but only for fields added by Connect apps.	GET /rest/api/2/field/{fieldKey}/option/{optionId}
Update select list issue field option (added by app)	Updates or creates an option for a select list issue field, but only for fields added by Connect apps.	PUT /rest/api/2/field/{fieldKey}/option/{optionId}

Issue custom field options (apps) (version 3)

Name	Description	API docs link
Get all options for a issue field	Returns a list of all the options of a select list in an issue field	GET /rest/api/3/field/{fieldKey}/option

Create issue field option	Creates an option for a select list issue field.	POST /rest/api/3/field/{fieldKey}/option
Get options for issue field	Returns the options from a select list issue field, but only for fields added by Connect apps.	GET /rest/api/3/field/{fieldKey}/option/{optionId}
Update select list issue field option (added by app)	Updates or creates an option for a select list issue field, but only for fields added by Connect apps.	PUT /rest/api/3/field/{fieldKey}/option/{optionId}
Delete issue field option (added by app)	Deletes an option from a select list issue field, but only for fields added by Connect apps.	DELETE /rest/api/3/field/{fieldKey}/option/{optionId}

Issue field configurations (version 2)

Name	Description	API docs link
Get all field configurations	Returns a list of field configurations. Only field configurations used in company-managed (classic) projects are returned.	GET /rest/api/2/fieldconfiguration
Create a field configuration	Creates a field configuration with the default field properties, with all the fields being optional. Can only be used with company managed (classic) projects.	POST /rest/api/2/fieldconfiguration
Delete a field configuration	Deletes a field configuration. Can only be used with company managed (classic) projects.	DELETE /rest/api/2/fieldconfiguration/{id}
Update a field configuration	Updates a field configuration. Can only be used with company managed (classic) projects.	PUT /rest/api/2/fieldconfiguration/{id}
Get field configuration items	Returns a list of all the fields for a configuration, such as id, description, isHidden, isRequired. Can only be used with company managed (classic) projects.	GET /rest/api/2/fieldconfiguration/{id}/fields
Update field configuration items	Updates fields in a field configuration, using provided values to override the existing values. Can only be used with company managed (classic) projects.	PUT /rest/api/2/fieldconfiguration/{id}/fields
Get all field configuration schemes	Returns a list of field configuration schemes, including fields like id, name, and description. Can only be used with company managed (classic) projects.	GET /rest/api/2/fieldconfigurationscheme
Create a field configuration scheme	Create a field configuration scheme. Can only be used with company managed (classic) projects.	POST /rest/api/2/fieldconfigurationscheme

Get field configuration issue type items	Returns a list of field configuration issue type items. Can only be used with company managed (classic) projects.	GET /rest/api/2/fieldconfigurationscheme/mapping
Get field configuration schemes for projects	Returns a list of field configuration schemes and for each, a list of the projects that use it. Can only be used in company managed (classic) projects.	GET /rest/api/2/fieldconfigurationscheme/project
Assign a field configuration scheme to a project	Assigns a field configuration scheme to a project. Can only be used with company managed (classic) projects.	PUT /rest/api/2/fieldconfigurationscheme/project
Delete a field configuration scheme	Deletes a field configuration scheme. Can only be used with company managed (classic) projects.	DELETE /rest/api/2/fieldconfigurationscheme/{id}
Update a field configuration scheme	Updates a field configuration scheme. Can only be used with company managed (classic) projects.	PUT /rest/api/2/fieldconfigurationscheme/{id}
Assign issue types to field configurations	Assigns issue types to field configurations on field configuration scheme. Can only be used with company managed (classic) projects.	PUT /rest/api/2/fieldconfigurationscheme/{id}/mapping
Remove issue types from a field configuration scheme	Removes issue types from the field configuration scheme. Can only be used with company managed (classic) projects.	POST /rest/api/2/fieldconfigurationscheme/{id}/mapping/delete

Issue field configurations (version 3)

Name	Description	API docs link
Get all field configurations	Returns a list of field configurations. Only field configurations used in company-managed (classic) projects are returned.	GET /rest/api/3/fieldconfiguration
Create a field configuration	Creates a field configuration with the default field properties, with all the fields being optional. Can only be used with company managed (classic) projects.	POST /rest/api/3/fieldconfiguration
Update a field configuration	Updates a field configuration. Can only be used with company managed (classic) projects.	PUT /rest/api/3/fieldconfiguration/{id}
Delete a field configuration	Deletes a field configuration. Can only be used with company managed (classic) projects.	DELETE /rest/api/3/fieldconfiguration/{id}
Get field configuration items	Returns a list of all the fields for a configuration, such as id, description, isHidden, isRequired. Can only be used with company managed (classic) projects.	GET /rest/api/3/fieldconfiguration/{id}/fields

Update field configuration items	Updates fields in a field configuration, using provided values to override the existing values. Can only be used with company managed (classic) projects.	PUT /rest/api/3/fieldconfiguration/{id}/fields
Get all field configuration schemes	Returns a list of field configuration schemes, including fields like id, name, and description. Can only be used with company managed (classic) projects.	GET /rest/api/3/fieldconfigurationscheme
Create a field configuration scheme	Create a field configuration scheme. Can only be used with company managed (classic) projects.	POST /rest/api/3/fieldconfigurationscheme
Get field configuration issue type items	Returns a list of field configuration issue type items. Can only be used with company managed (classic) projects.	GET /rest/api/3/fieldconfigurationscheme/mapping
Get field configuration schemes for projects	Returns a list of field configuration schemes and for each, a list of the projects that use it. Can only be used in company managed (classic) projects.	GET /rest/api/3/fieldconfigurationscheme/project
Assign a field configuration scheme to a project	Assigns a field configuration scheme to a project. Can only be used with company managed (classic) projects.	PUT /rest/api/3/fieldconfigurationscheme/project
Update a field configuration scheme	Updates a field configuration scheme. Can only be used with company managed (classic) projects.	PUT /rest/api/3/fieldconfigurationscheme/{id}
Delete a field configuration scheme	Deletes a field configuration scheme. Can only be used with company managed (classic) projects.	DELETE /rest/api/3/fieldconfigurationscheme/{id}
Assign issue types to field configurations	Assigns issue types to field configurations on field configuration scheme. Can only be used with company managed (classic) projects.	PUT /rest/api/3/fieldconfigurationscheme/{id}/mapping
Remove issue types from a field configuration scheme	Removes issue types from the field configuration scheme. Can only be used with company managed (classic) projects.	POST /rest/api/3/fieldconfigurationscheme/{id}/mapping/delete

Issue fields (version 2)

Name	Description	API docs link
Get issue fields	Returns all of an issue's system fields and custom fields. This operation can be accessed anonymously.	GET /rest/api/2/field
Create custom field	Creates a custom field.	POST /rest/api/2/field

Get project fields	Returns a list of fields for Classic Jira projects.	GET /rest/api/2/field/search
Get project fields in trash	Returns a list of project fields in the trash.	GET /rest/api/2/field/search/trashed
Update custom field	Updates a custom field.	PUT /rest/api/2/field/{fieldId}
Get field contexts DEPRECATED	Returns a list of all contexts in which a field is used.	GET /rest/api/2/field/{fieldId}/contexts
Restore a custom field from trash	Restores a custom field from trash.	POST /rest/api/2/field/{id}/restore
Move a custom field to trash	Moves a custom field to trash.	POST /rest/api/2/field/{id}/trash

Issue fields (version 3)

Name	Description	API docs link
Get issue fields	Returns all of an issue's system fields and custom fields. This operation can be accessed anonymously.	GET /rest/api/3/field
Create custom field	Creates a custom field.	POST /rest/api/3/field
Get project fields	Returns a list of fields for Classic Jira projects.	GET /rest/api/3/field/search
Get project fields in trash	Returns a list of project fields in the trash.	GET /rest/api/3/field/search/trashed
Update custom field	Updates a custom field.	PUT /rest/api/3/field/{fieldId}
Get field contexts DEPRECATED	Returns a list of all contexts in which a field is used.	GET /rest/api/3/field/{fieldId}/contexts
Restore a custom field from trash	Restores a custom field from trash.	POST /rest/api/3/field/{id}/restore
Move a custom field to trash	Moves a custom field to trash.	POST /rest/api/3/field/{id}/trash

Issue link types (version 2)

Name	Description	API docs link
------	-------------	---------------

Get issue link types	Returns a list of all issue link types.	GET /rest/api/2/issueLinkType
Create issue link type	Creates an issue link type, which is used to provide descriptions explaining the reasons why issues are linked.	POST /rest/api/2/issueLinkType
Delete issue link type	Deletes an issue link type.	DELETE /rest/api/2/issueLinkType/{issueLinkTypeId}
Get issue link types	Returns an issue link type.	GET /rest/api/2/issueLinkType/{issueLinkTypeId}
Update issue link type	Updates an issue link type.	PUT /rest/api/2/issueLinkType/{issueLinkTypeId}

Issue link types (version 3)

Name	Description	API docs link
Get issue link types	Returns a list of all issue link types.	GET /rest/api/3/issueLinkType
Create issue link type	Creates an issue link type, which is used to provide descriptions explaining the reasons why issues are linked.	POST /rest/api/3/issueLinkType
Get issue link types	Returns an issue link type.	GET /rest/api/3/issueLinkType/{issueLinkTypeId}
Update issue link type	Updates an issue link type.	PUT /rest/api/3/issueLinkType/{issueLinkTypeId}
Delete issue link type	Deletes an issue link type.	DELETE /rest/api/3/issueLinkType/{issueLinkTypeId}

Issue navigator settings (version 2)

Name	Description	API docs link
Get issue navigator default columns	Returns the default columns of the issue navigator.	GET /rest/api/2/settings/columns
Set issue navigator default columns	Sets the default columns of the issue navigator.	PUT /rest/api/2/settings/columns

Issue navigator settings (version 3)

Name	Description	API docs link
Get issue navigator default columns	Returns the default columns of the issue navigator.	GET /rest/api/3/settings/columns

Set issue navigator default columns	Sets the default columns of the issue navigator.	PUT /rest/api/3/settings/columns
-------------------------------------	--	----------------------------------

Issue notification schemes (version 2)

Name	Description	API docs link
Get notification schemes paginated	Returns a paginated list of notifications schemes.	GET /rest/api/2/notificationscheme
Crate notification scheme	Creates a notification scheme.	POST /rest/api/2/notificationscheme
Get projects by notification scheme paginated	Returns a paginated list of projects that have the provided notification scheme assigned.	GET /rest/api/2/notificationscheme/project
Get notification scheme	Returns a notification scheme and its details.	GET /rest/api/2/notificationscheme/{id}
Update notification scheme	Updates a notification scheme.	PUT /rest/api/2/notificationscheme/{id}
Add notifications to notification scheme	Adds notifications to a notification scheme.	PUT /rest/api/2/notificationscheme/{id}/notification
Delete notification scheme	Deletes a notification scheme.	DELETE /rest/api/2/notificationscheme/{notificationSchemeId}
Remove notification from notification scheme	Removes a notification from a notification scheme.	DELETE /rest/api/2/notificationscheme/{notificationSchemeId}/notification/{notificationId}

Issue notification schemes (version 3)

Name	Description	API docs link
Get notification schemes paginated	Returns a paginated list of notifications schemes.	GET /rest/api/3/notificationscheme
Crate notification scheme	Creates a notification scheme.	POST /rest/api/3/notificationscheme
Get projects by notification scheme paginated	Returns a paginated list of projects that have the provided notification scheme assigned.	GET /rest/api/3/notificationscheme/project
Get notification scheme	Returns a notification scheme and its details.	GET /rest/api/3/notificationscheme/{id}

Update notification scheme	Updates a notification scheme.	PUT /rest/api/3/notificationscheme/{id}
Add notifications to notification scheme	Adds notifications to a notification scheme.	PUT /rest/api/3/notificationscheme/{id}/notification
Delete notification scheme	Deletes a notification scheme.	DELETE /rest/api/3/notificationscheme/{notificationSchemeId}
Remove notification from notification scheme	Removes a notification from a notification scheme.	DELETE /rest/api/3/notificationscheme/{notificationSchemeId}/notification/{notificationId}

Issue priorities (version 2)

Name	Description	API docs link
Get priorities	Returns a list of all issue priorities.	GET /rest/api/2/priority
Create priority	Creates an issue priority.	POST /rest/api/2/priority
Set default priority	Sets a default issue priority.	PUT /rest/api/2/priority/default
Move priorities	Changes the order of issue priorities.	PUT /rest/api/2/priority/move
Search priorities	Returns a list of priorities based on the provided priority IDs, project IDs, and whether the field configuration is default.	GET /rest/api/2/priority/search
Delete priority	Deletes an issue priority.	DELETE /rest/api/2/priority/{id}
Get priority	Returns an issue priority.	GET /rest/api/2/priority/{id}
Update priority	Updates an issue priority.	PUT /rest/api/2/priority/{id}

Issue priorities (version 3)

Name	Description	API docs link
Get priorities DEPRECATED	Returns a list of all issue priorities.	GET /rest/api/3/priority
Create priority	Creates an issue priority.	POST /rest/api/3/priority

Set default priority	Sets a default issue priority.	PUT /rest/api/3/priority/default
Move priorities	Changes the order of issue priorities.	PUT /rest/api/3/priority/move
Search priorities	Returns a list of priorities based on the provided priority IDs, project IDs, and whether the field configuration is default.	GET /rest/api/3/priority/search
Get priority	Returns an issue priority.	GET /rest/api/3/priority/{id}
Update priority	Updates an issue priority.	PUT /rest/api/3/priority/{id}
Delete priority DEPRECATED	Deletes an issue priority.	DELETE /rest/api/3/priority/{id}

Issue resolutions (version 2)

Name	Description	API docs link
Get resolutions	Returns a list of all issue resolution values.	GET /rest/api/2/resolution
Create resolution	Creates an issue resolution.	POST /rest/api/2/resolution
Set default resolution	Sets a default issue resolution.	PUT /rest/api/2/resolution/default
Move resolutions	Changes the order of issue resolutions.	PUT /rest/api/2/resolution/move
Search resolutions	Returns a list of resolution values based on the provided IDs and on whether the resolutions are default ones.	GET /rest/api/2/resolution/search
Delete resolution	Deletes an issue resolution value.	DELETE /rest/api/2/resolution/{id}
Get resolution	Returns an issue resolution value.	GET /rest/api/2/resolution/{id}
Update resolution	Updates an issue resolution value.	PUT /rest/api/2/resolution/{id}

Issue resolutions (version 3)

Name	Description	API docs link
------	-------------	---------------

Get resolutions DEPRECATED	Returns a list of all issue resolution values.	GET /rest/api/3/resolution
Create resolution	Creates an issue resolution.	POST /rest/api/3/resolution
Set default resolution	Sets a default issue resolution.	PUT /rest/api/3/resolution/default
Move resolutions	Changes the order of issue resolutions.	PUT /rest/api/3/resolution/move
Search resolutions	Returns a list of resolution values based on the provided IDs and on whether the resolutions are default ones.	GET /rest/api/3/resolution/search
Get resolution	Returns an issue resolution value.	GET /rest/api/3/resolution/{id}
Update resolution	Updates an issue resolution value.	PUT /rest/api/3/resolution/{id}
Delete resolution	Deletes an issue resolution value.	DELETE /rest/api/3/resolution/{id}

Issue security level (version 2)

Name	Description	API docs link
Get issue security level members	Returns issue security level members.	GET /rest/api/2/issuesecurityschemes/{issueSecuritySchemeld}/members
Get an issue security level	Returns the details of an issue security level that is part of an issue security scheme, including its name, description, and whether it is the default security level within that scheme.	GET /rest/api/2/securitylevel/{id}

Issue security level (version 3)

Name	Description	API docs link
Get issue security level members	Returns issue security level members.	GET /rest/api/3/issuesecurityschemes/{issueSecuritySchemeld}/members

Get an issue security level	Returns the details of an issue security level that is part of an issue security scheme, including its name, description, and whether it is the default security level within that scheme.	GET /rest/api/3/securitylevel/{id}
-----------------------------	--	------------------------------------

Issue security schemes (version 2)

Name	Description	API docs link
Get issue security schemes	Returns all issue security schemes.	GET /rest/api/2/issuesecurityschemes
Create issue security scheme	Creates a security scheme with security scheme levels and levels' members.	POST /rest/api/2/issuesecurityschemes
Get issue security levels	Returns a paginated list of issue security levels.	GET /rest/api/2/issuesecurityschemes/level
Set default issue security levels	Sets default issue security levels for schemes.	PUT /rest/api/2/issuesecurityschemes/level/default
Get issue security level members	Returns a paginated list of issue security level members.	GET /rest/api/2/issuesecurityschemes/level/member
Get projects using issue security schemes	Returns a paginated mapping of projects that are using security schemes.	GET /rest/api/2/issuesecurityschemes/project
Associate security scheme to project	Associates an issue security scheme with a project and if provided, remaps security levels of issues to the new levels,	PUT /rest/api/2/issuesecurityschemes/project
Search issue security schemes	Returns a paginated list of issue security schemes.	GET /rest/api/2/issuesecurityschemes/search
Get issue security schemes	Returns an issue security scheme along with its security levels.	GET /rest/api/2/issuesecurityschemes/{id}
Update issue security scheme	Updates the issue security scheme.	PUT /rest/api/2/issuesecurityschemes/{id}
Delete issue security scheme	Deletes an issue security scheme.	DELETE /rest/api/2/issuesecurityschemes/{schemelid}

Add issue security levels	Adds levels and levels' members to the issue security scheme.	PUT /rest/api/2/issuesecurityschemes/{schemelId}/level
Remove issue security level	Deletes an issue security level.	DELETE /rest/api/2/issuesecurityschemes/{schemelId}/level/{levelId}
Update issue security level	Updates the issue security level.	PUT /rest/api/2/issuesecurityschemes/{schemelId}/level/{levelId}
Add issue security level members	Adds members to the issue security level.	PUT /rest/api/2/issuesecurityschemes/{schemelId}/level/{levelId}/member
Remove member from issue security level	Removes an issue security level member from an issue security scheme.	DELETE /rest/api/2/issuesecurityschemes/{schemelId}/level/{levelId}/member/{memberId}

Issue security schemes (version 3)

Name	Description	API docs link
Get issue security schemes	Returns all issue security schemes.	GET /rest/api/3/issuesecurityschemes
Create issue security scheme	Creates a security scheme with security scheme levels and levels' members.	POST /rest/api/3/issuesecurityschemes
Get issue security levels	Returns a paginated list of issue security levels.	GET /rest/api/3/issuesecurityschemes/level
Set default issue security levels	Sets default issue security levels for schemes.	PUT /rest/api/3/issuesecurityschemes/level/default
Get issue security level members	Returns a paginated list of issue security level members.	GET /rest/api/3/issuesecurityschemes/level/member
Get projects using issue security schemes	Returns a paginated mapping of projects that are using security schemes.	GET /rest/api/3/issuesecurityschemes/project
Associate security scheme to project	Associates an issue security scheme with a project and if provided, remaps security levels of issues to the new levels,	PUT /rest/api/3/issuesecurityschemes/project

Search issue security schemes	Returns a paginated list of issue security schemes.	GET /rest/api/3/issuesecurityschemes/search
Get issue security schemes	Returns an issue security scheme along with its security levels.	GET /rest/api/3/issuesecurityschemes/{id}
Update issue security scheme	Updates the issue security scheme.	PUT /rest/api/3/issuesecurityschemes/{id}
Delete issue security scheme	Deletes an issue security scheme.	DELETE /rest/api/3/issuesecurityschemes/{schemeld}
Add issue security levels	Adds levels and levels' members to the issue security scheme.	PUT /rest/api/3/issuesecurityschemes/{schemeld}/level
Update issue security level	Updates the issue security level.	PUT /rest/api/3/issuesecurityschemes/{schemeld}/level/{levelld}
Remove issue security level	Deletes an issue security level.	DELETE /rest/api/3/issuesecurityschemes/{schemeld}/level/{levelld}
Add issue security level members	Adds members to the issue security level.	PUT /rest/api/3/issuesecurityschemes/{schemeld}/level/{levelld}/member
Remove member from issue security level	Removes an issue security level member from an issue security scheme.	DELETE /rest/api/3/issuesecurityschemes/{schemeld}/level/{levelld}/member/{memberld}

Issue properties (version 2)

Name	Description	API docs link
Get issue type property keys	Returns all the property keys of the issue type.	GET /rest/api/2/issuetype/{issueTypeld}/properties
Delete issue type property	Deletes the issue type property.	DELETE /rest/api/2/issuetype/{issueTypeld}/properties/{propertyKey}
Get issue type property keys	Returns the key and value of the issue type property.	GET /rest/api/2/issuetype/{issueTypeld}/properties/{propertyKey}
Set issue type property	Creates or updates the value of the issue type property.	PUT /rest/api/2/issuetype/{issueTypeld}/properties/{propertyKey}

Issue properties (version 3)

Name	Description	API docs link
Get issue type property keys	Returns all the property keys of the issue type.	GET /rest/api/3/issuetype/{issueTypeId}/properties
Get issue type property keys	Returns the key and value of the issue type property.	GET /rest/api/3/issuetype/{issueTypeId}/properties/{propertyKey}
Set issue type property	Creates or updates the value of the issue type property.	PUT /rest/api/3/issuetype/{issueTypeId}/properties/{propertyKey}
Delete issue type property	Deletes the issue type property.	DELETE /rest/api/3/issuetype/{issueTypeId}/properties/{propertyKey}

Issue type schemes (version 2)

Name	Description	API docs link
Get all issue type schemes	Returns a paginated list of issue-type schemes.	GET /rest/api/2/issuetypescheme
Create issue type scheme	Creates an issue type scheme.	POST /rest/api/2/issuetypescheme
Get issue type scheme items	Returns a paginated list of issue type scheme items.	GET /rest/api/2/issuetypescheme/mapping
Get issue type schemes for projects	Returns a paginated list of issue-type schemes and, for each issue-type scheme, a list of the projects that use it.	GET /rest/api/2/issuetypescheme/project
Assign issue type scheme to project	Assign issue type scheme to project	PUT /rest/api/2/issuetypescheme/project
Delete issue type scheme	Deletes an issue type scheme.	DELETE /rest/api/2/issuetypescheme/{issueTypeSchemeId}
Update issue type scheme	Updates an issue type scheme.	PUT /rest/api/2/issuetypescheme/{issueTypeSchemeId}
Add issue types to issue type scheme	Adds issue types to an issue type scheme.	PUT /rest/api/2/issuetypescheme/{issueTypeSchemeId}/issuetype
Change order of issue types	Changes the order of issue types in an issue type scheme.	PUT /rest/api/2/issuetypescheme/{issueTypeSchemeId}/issuetype/move
Remove issue type from issue type scheme	Removes an issue type from an issue type scheme.	DELETE /rest/api/2/issuetypescheme/{issueTypeSchemeId}/issuetype/{issueTypeId}

Issue type schemes (version 3)

Name	Description	API docs link
Get all issue type schemes	Returns a paginated list of issue-type schemes.	GET /rest/api/3/issuetypescheme
Create issue type scheme	Creates an issue type scheme.	POST /rest/api/3/issuetypescheme
Get issue type scheme items	Returns a paginated list of issue type scheme items.	GET /rest/api/3/issuetypescheme/mapping
Get issue type schemes for projects	Returns a paginated list of issue-type schemes and, for each issue-type scheme, a list of the projects that use it.	GET /rest/api/3/issuetypescheme/project
Assign issue type scheme to project	Assign issue type scheme to project	PUT /rest/api/3/issuetypescheme/project
Update issue type scheme	Updates an issue type scheme.	PUT /rest/api/3/issuetypescheme/{issueTypeSchemeId}
Delete issue type scheme	Deletes an issue type scheme.	DELETE /rest/api/3/issuetypescheme/{issueTypeSchemeId}
Add issue types to issue type scheme	Adds issue types to an issue type scheme.	PUT /rest/api/3/issuetypescheme/{issueTypeSchemeId}/issuetype
Change order of issue types	Changes the order of issue types in an issue type scheme.	PUT /rest/api/3/issuetypescheme/{issueTypeSchemeId}/issuetype/move
Remove issue type from issue type scheme	Removes an issue type from an issue type scheme.	DELETE /rest/api/3/issuetypescheme/{issueTypeSchemeId}/issuetype/{issueTypeId}

Issue type screen schemes (version 2)

Name	Description	API docs link
Get issue type screen schemes	Returns a paginated list of issue type screen schemes.	GET /rest/api/2/issuetypescreenscheme

Create issue type screen scheme	Creates an issue type screen scheme.	POST /rest/api/2/issuetypescreenscheme
Get issue type screen scheme items	Returns a paginated list of issue type screen scheme items.	GET /rest/api/2/issuetypescreenscheme/mapping
Get issue type screen schemes for projects	Returns a pagination list of issue-type screen schemes and, for each issue-type screen scheme, a list of the projects that use it.	GET /rest/api/2/issuetypescreenscheme/project
Assign issue type screen scheme to project	Assigns an issue type screen scheme to a project.	PUT /rest/api/2/issuetypescreenscheme/project
Delete issue type screen scheme	Deletes an issue type screen scheme.	DELETE /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}
Update issue type screen scheme	Updates an issue type screen scheme.	PUT /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}
Append mappings to issue type screen scheme	Appends issue type to screen scheme mappings to an issue type screen scheme.	PUT /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping
Update issue type screen scheme default screen scheme	Updates the default screen scheme of an issue-type screen scheme. The default screen scheme is used for all unmapped issue types.	PUT /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping/default
Remove mappings from issue type screen scheme	Removes issue type to screen scheme mappings from an issue type screen scheme.	POST /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping/remove
Get issue type screen scheme projects	Returns a paginated list of projects associated with an issue type screen scheme.	GET /rest/api/2/issuetypescreenscheme/{issueTypeScreenSchemeId}/project

Issue type screen schemes (version 3)

Name	Description	API docs link
Get issue type screen schemes	Returns a paginated list of issue type screen schemes.	GET /rest/api/3/issuetypescreenscheme

Create issue type screen scheme	Creates an issue type screen scheme.	POST /rest/api/3/issuetypescreenscheme
Get issue type screen scheme items	Returns a paginated list of issue type screen scheme items.	GET /rest/api/3/issuetypescreenscheme/mapping
Get issue type screen schemes for projects	Returns a pagination list of issue-type screen schemes and, for each issue-type screen scheme, a list of the projects that use it.	GET /rest/api/3/issuetypescreenscheme/project
Assign issue type screen scheme to project	Assigns an issue type screen scheme to a project.	PUT /rest/api/3/issuetypescreenscheme/project
Update issue type screen scheme	Updates an issue type screen scheme.	PUT /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}
Delete issue type screen scheme	Deletes an issue type screen scheme.	DELETE /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}
Append mappings to issue type screen scheme	Appends issue type to screen scheme mappings to an issue type screen scheme.	PUT /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping
Update issue type screen scheme default screen scheme	Updates the default screen scheme of an issue-type screen scheme. The default screen scheme is used for all unmapped issue types.	PUT /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping/default
Remove mappings from issue type screen scheme	Removes issue type to screen scheme mappings from an issue type screen scheme.	POST /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}/mapping/remove
Get issue type screen scheme projects	Returns a paginated list of projects associated with an issue type screen scheme.	GET /rest/api/3/issuetypescreenscheme/{issueTypeScreenSchemeId}/project

Issue types (version 2)

Name	Description	API docs link
Get all issue types for user	Returns all issue types by user.	GET /rest/api/2/issuetype
Create issue type	Creates an issue type and adds it to the default issue type scheme.	POST /rest/api/2/issuetype

Get issue types for project	Returns issue types for a project.	GET /rest/api/2/issuetype/project
Delete issue type	Deletes the issue type. If the issue type is in use, uses are updated with the alternative issue type (`alternativeIssueTypeId`).	DELETE /rest/api/2/issuetype/{id}
Get issue types for project	Returns an issue type for a project.	GET /rest/api/2/issuetype/{id}
Update issue type	Updates the issue type.	PUT /rest/api/2/issuetype/{id}
Get alternative issue types	Returns a list of issue types that can be used to replace the issue type.	GET /rest/api/2/issuetype/{id}/alternatives
Load issue type avatar	Loads an avatar for the issue type.	POST /rest/api/2/issuetype/{id}/avatar2

Issue types (version 3)

Name	Description	API docs link
Get all issue types for user	Returns all issue types by user.	GET /rest/api/3/issuetype
Create issue type	Creates an issue type and adds it to the default issue type scheme.	POST /rest/api/3/issuetype
Get issue types for project	Returns issue types for a project.	GET /rest/api/3/issuetype/project
Get issue types for project	Returns an issue type for a project.	GET /rest/api/3/issuetype/{id}
Update issue type	Updates the issue type.	PUT /rest/api/3/issuetype/{id}
Delete issue type	Deletes the issue type. If the issue type is in use, uses are updated with the alternative issue type (`alternativeIssueTypeId`).	DELETE /rest/api/3/issuetype/{id}
Get alternative issue types	Returns a list of issue types that can be used to replace the issue type.	GET /rest/api/3/issuetype/{id}/alternatives
Load issue type avatar	Loads an avatar for the issue type.	POST /rest/api/3/issuetype/{id}/avatar2

Issue watchers (version 2)

Name	Description	API docs link
Get bulk watched issues	Returns the details of the watched status of issues from a list. If an issue ID is invalid, the returned watched status will be `false`.	POST /rest/api/2/issue/watching

Issue watchers (version 3)

Name	Description	API docs link
Get bulk watched issues	Returns the details of the watched status of issues from a list. If an issue ID is invalid, the returned watched status will be `false`.	POST /rest/api/3/issue/watching

Issue worklog properties (version 2)

Name	Description	API docs link
Delete worklog property	Deletes a worklog property.	DELETE /rest/api/2/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}
Get worklog property keys	Returns the value of a worklog property.	GET /rest/api/2/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}
Set worklog property	Sets the value of a worklog property. Use this operation to store custom data against the worklog.	PUT /rest/api/2/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}

Issue worklog properties (version 3)

Name	Description	API docs link
Get worklog property keys	Returns the value of a worklog property.	GET /rest/api/3/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}
Set worklog property	Sets the value of a worklog property. Use this operation to store custom data against the worklog.	PUT /rest/api/3/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}
Delete worklog property	Deletes a worklog property.	DELETE /rest/api/3/issue/{issueIdOrKey}/worklog/{worklogId}/properties/{propertyKey}

Issue worklogs (version 2)

Name	Description	API docs link
Get IDs of deleted worklogs	Returns a list of IDs and delete timestamps for worklogs deleted after a date and time.	GET /rest/api/2/worklog/deleted

Issue worklogs (version 3)

Name	Description	API docs link
Get IDs of deleted worklogs	Returns a list of IDs and delete timestamps for worklogs deleted after a date and time.	GET /rest/api/3/worklog/deleted

Issues (version 2)

Name	Description	API docs link
Get issue events	Returns all issue events.	GET /rest/api/2/events

Issues (version 3)

Name	Description	API docs link
Get issue events	Returns all issue events.	GET /rest/api/3/events

Jira expressions (version 2)

Name	Description	API docs link
Validates Jira expressions	Checks the validity of a Jira expression.	POST /rest/api/2/expression/analyse

Jira expressions (version 3)

Name	Description	API docs link
Validates Jira expressions	Checks the validity of a Jira expression.	POST /rest/api/3/expression/analyse

Jira settings (version 2)

Created in 2024 by Atlassian

Name	Description	API docs link
Get application property	Returns all editable application properties.	GET /rest/api/2/application-properties
Get advanced settings	Returns all application properties that are accessible from the Advanced Settings page.	GET /rest/api/2/application-properties/advanced-settings
Set application property	Updates the value of an application property.	PUT /rest/api/2/application-properties/{id}
Get global settings	Returns the Jira instance's global settings; these settings determine whether optional features (like subtasks and time tracking) are enabled. If time time tracking is enabled, this operation also returns the time tracking configuration.	GET /rest/api/2/configuration

Jira settings (version 3)

Name	Description	API docs link
Get application property	Returns all editable application properties.	GET /rest/api/3/application-properties
Get advanced settings	Returns all application properties that are accessible from the Advanced Settings page.	GET /rest/api/3/application-properties/advanced-settings
Set application property	Updates the value of an application property.	PUT /rest/api/3/application-properties/{id}
Get global settings	Returns the Jira instance's global settings; these settings determine whether optional features (like subtasks and time tracking) are enabled. If time time tracking is enabled, this operation also returns the time tracking configuration.	GET /rest/api/3/configuration

JQL (version 2)

Name	Description	API docs link
Get field reference data (GET)	Returns reference data for JQL searches. Users can filter visible field details by project or collapse non-unique fields by field type.	GET /rest/api/2/jql/autocomplete
Get field reference data (POST)	Returns reference data for JQL searches. Users can filter the custom fields returned by the project.	POST /rest/api/2/jql/autocomplete
Convert user identifiers to account IDs in JQL queries	Converts the user names and user keys in the provided JQL query to account IDs.	POST /rest/api/2/jql/pdcleaner

JQL (version 3)

Name	Description	API docs link
Get field reference data (GET)	Returns reference data for JQL searches. Users can filter visible field details by project or collapse non-unique fields by field type.	GET /rest/api/3/jql/autocomplete/data
Get field reference data (POST)	Returns reference data for JQL searches. Users can filter the custom fields returned by the project.	POST /rest/api/3/jql/autocomplete/data
Convert user identifiers to account IDs in JQL queries	Converts the user names and user keys in the provided JQL query to account IDs.	POST /rest/api/3/jql/pdcleaner

JQL functions (apps) (version 2)

Name	Description	API docs link
Get precomputations for a custom JQL function	Returns the list of precomputations (mappings of custom JQL functions to native JQL) for a custom JQL function.	GET /rest/api/2/jql/function/computation
Update precomputations for a custom JQL function	Updates precomputations (mappings of custom JQL functions to native JQL) for a custom JQL function.	POST /rest/api/2/jql/function/computation

JQL functions (apps) (version 3)

Name	Description	API docs link
Get precomputations for a custom JQL function	Returns the list of precomputations (mappings of custom JQL functions to native JQL) for a custom JQL function.	GET /rest/api/3/jql/function/computation
Update precomputations for a custom JQL function	Updates precomputations (mappings of custom JQL functions to native JQL) for a custom JQL function.	POST /rest/api/3/jql/function/computation

License metrics (version 2)

Name	Description	API docs link
Get license	Returns the license details of a Jira instance.	GET /rest/api/2/instance/license

Get approximate license count	Returns the approximate number of user accounts across all Jira licenses.	GET /rest/api/2/license/approximateLicenseCount
Get approximate application license count	Returns the approximate number of user accounts for a single Jira license.	GET /rest/api/2/license/approximateLicenseCount/product/{applicationKey}

License metrics (version 3)

Name	Description	API docs link
Get license	Returns the license details of a Jira instance.	GET /rest/api/3/instance/license
Get approximate license count	Returns the approximate number of user accounts across all Jira licenses.	GET /rest/api/3/license/approximateLicenseCount
Get approximate application license count	Returns the approximate number of user accounts for a single Jira license.	GET /rest/api/3/license/approximateLicenseCount/product/{applicationKey}

Myself (version 2)

Name	Description	API docs link
Delete preference	Deletes the value of a user's preference setting.	DELETE /rest/api/2/mypreferences
Get preference	Get the value of a user's preference setting.	GET /rest/api/2/mypreferences
Set preference	Set the value of a user's preference setting.	PUT /rest/api/2/mypreferences
Delete locale DEPRECATED	Removes a user's locale.	DELETE /rest/api/2/mypreferences/locale
Get locale	Returns the user's locale.	GET /rest/api/2/mypreferences/locale
Set locale DEPRECATED	Sets a user's locale.	PUT /rest/api/2/mypreferences/locale
Get current user	Returns the details of the current user.	GET /rest/api/2/myself

Myself (version 3)

Name	Description	API docs link
Get preference	Get the value of a user's preference setting.	GET /rest/api/3/mypreferences
Set preference	Set the value of a user's preference setting.	PUT /rest/api/3/mypreferences
Delete preference	Deletes the value of a user's preference setting.	DELETE /rest/api/3/mypreferences
Get locale	Returns the user's locale.	GET /rest/api/3/mypreferences/locale
Set locale DEPRECATED	Sets a user's locale.	PUT /rest/api/3/mypreferences/locale
Delete locale DEPRECATED	Removes a user's locale.	DELETE /rest/api/3/mypreferences/locale
Get current user	Returns the details of the current user.	GET /rest/api/3/myself

Permission schemes (version 2)

Name	Description	API docs link
Get all permission schemes	Returns all permission schemes.	GET /rest/api/2/permissionscheme
Create permission scheme	Creates a new permission scheme.	POST /rest/api/2/permissionscheme
Delete permission scheme	Delete a permission scheme.	DELETE /rest/api/2/permissionscheme/{schemeld}
Get permission scheme	Returns a permission scheme.	GET /rest/api/2/permissionscheme/{schemeld}
Update permission scheme	Updates a permission scheme.	PUT /rest/api/2/permissionscheme/{schemeld}
Get permission scheme grants	Returns all permission grants for a permission scheme.	GET /rest/api/2/permissionscheme/{schemeld}/permission
Create permission grant	Creates a permission grant in a permission scheme.	POST /rest/api/2/permissionscheme/{schemeld}/permission
Delete permission scheme grant	Deletes a permission scheme grant.	DELETE /rest/api/2/permissionscheme/{schemeld}/permission/{permissionId}
Get permission scheme grant	Returns a permission scheme grant.	GET /rest/api/2/permissionscheme/{schemeld}/permission/{permissionId}

Permission schemes (version 3)

Name	Description	API docs link
Get all permission schemes	Returns all permission schemes.	GET /rest/api/3/permissionscheme
Create permission scheme	Creates a new permission scheme.	POST /rest/api/3/permissionscheme
Get permission scheme	Returns a permission scheme.	GET /rest/api/3/permissionscheme/{schemeld}
Update permission scheme	Updates a permission scheme.	PUT /rest/api/3/permissionscheme/{schemeld}
Delete permission scheme	Delete a permission scheme.	DELETE /rest/api/3/permissionscheme/{schemeld}
Get permission scheme grants	Returns all permission grants for a permission scheme.	GET /rest/api/3/permissionscheme/{schemeld}/permission
Create permission grant	Creates a permission grant in a permission scheme.	POST /rest/api/3/permissionscheme/{schemeld}/permission
Get permission scheme grant	Returns a permission scheme grant.	GET /rest/api/3/permissionscheme/{schemeld}/permission/{permissionId}
Delete permission scheme grant	Deletes a permission scheme grant.	DELETE /rest/api/3/permissionscheme/{schemeld}/permission/{permissionId}

Permissions (version 2)

Name	Description	API docs link
Get all permissions	Returns a list of all global and project permissions.	GET /rest/api/2/permissions
Get permitted projects	Returns all projects where the user has permissions.	POST /rest/api/2/permissions/project

Permissions (version 3)

Name	Description	API docs link
Get all permissions	Returns a list of all global and project permissions.	GET /rest/api/3/permissions
Get permitted projects	Returns all projects where the user has permissions.	POST /rest/api/3/permissions/project

Project avatars (version 2)

Name	Description	API docs link
Set project avatar	Sets the avatar for a project.	PUT /rest/api/2/project/{projectIdOrKey}/avatar
Delete project avatar	Deletes a project's avatar.	DELETE /rest/api/2/project/{projectIdOrKey}/avatar/{id}
Load project avatar	Loads a project's avatar from the indicated location.	POST /rest/api/2/project/{projectIdOrKey}/avatar2
Get all project avatars	Returns all project avatars.	GET /rest/api/2/project/{projectIdOrKey}/avatars

Project avatars (version 3)

Name	Description	API docs link
Set project avatar	Sets the avatar for a project.	PUT /rest/api/3/project/{projectIdOrKey}/avatar
Delete project avatar	Deletes a project's avatar.	DELETE /rest/api/3/project/{projectIdOrKey}/avatar/{id}
Load project avatar	Loads a project's avatar from the indicated location.	POST /rest/api/3/project/{projectIdOrKey}/avatar2
Get all project avatars	Returns all project avatars.	GET /rest/api/3/project/{projectIdOrKey}/avatars

Project categories (version 2)

Name	Description	API docs link
Get all project categories	Returns all project categories.	GET /rest/api/2/projectCategory
Create project category	Creates a project category.	POST /rest/api/2/projectCategory
Delete project category	Deletes a project category.	DELETE /rest/api/2/projectCategory/{id}
Get project category by ID	Returns a project category.	GET /rest/api/2/projectCategory/{id}
Update project category	Updates a project category.	PUT /rest/api/2/projectCategory/{id}

Project categories (version 3)

Name	Description	API docs link
Get all project categories	Returns all project categories.	GET /rest/api/3/projectCategory

Create project category	Creates a project category.	POST /rest/api/3/projectCategory
Get project category by ID	Returns a project category.	GET /rest/api/3/projectCategory/{id}
Update project category	Updates a project category.	PUT /rest/api/3/projectCategory/{id}
Delete project category	Deletes a project category.	DELETE /rest/api/3/projectCategory/{id}

Project components (version 2)

Name	Description	API docs link
Create project component	Creates a project component (not a Compass component). Components can be used to provide containers for issues within a project. This operation can be accessed anonymously.	POST /rest/api/2/component
Delete project component	Deletes a project component. This operation can be accessed anonymously.	DELETE /rest/api/2/component/{id}
Get project component	Returns a project component. This operation can be accessed anonymously.	GET /rest/api/2/component/{id}
Update project component	Updates a project component (not a Compass component). This operation can be accessed anonymously.	PUT /rest/api/2/component/{id}
Get component issues count	Returns the issue counts assigned to the component. This operation can be accessed anonymously.	GET /rest/api/2/component/{id}/relatedIssueCounts
Get project components paginated	Returns a paginated list of all components in the provided project.	GET /rest/api/2/project/{projectIdOrKey}/component
Get project components	Returns a list of all components in the provided project.	GET /rest/api/2/project/{projectIdOrKey}/components

Project components (version 3)

Name	Description	API docs link
Create project component	Creates a project component (not a Compass component). Components can be used to provide containers for issues within a project. This operation can be accessed anonymously.	POST /rest/api/3/component

Get project component	Returns a project component. This operation can be accessed anonymously.	GET /rest/api/3/component/{id}
Update project component	Updates a project component (not a Compass component). This operation can be accessed anonymously.	PUT /rest/api/3/component/{id}
Delete project component	Deletes a project component. This operation can be accessed anonymously.	DELETE /rest/api/3/component/{id}
Get component issues count	Returns the issue counts assigned to the component. This operation can be accessed anonymously.	GET /rest/api/3/component/{id}/relatedIssueCounts
Get project components paginated	Returns a paginated list of all components in the provided project.	GET /rest/api/3/project/{projectIdOrKey}/component
Get project components	Returns a list of all components in the provided project.	GET /rest/api/3/project/{projectIdOrKey}/components

Project email (version 2)

Name	Description	API docs link
Get project's sender email	Returns the project's sender email address.	GET /rest/api/2/project/{projectId}/email
Set project's sender email	Sets the project's sender email address.	PUT /rest/api/2/project/{projectId}/email

Project email (version 3)

Name	Description	API docs link
Get project's sender email	Returns the project's sender email address.	GET /rest/api/3/project/{projectId}/email
Set project's sender email	Sets the project's sender email address.	PUT /rest/api/3/project/{projectId}/email

Project key and name validation (version 3)

Name	Description	API docs link
Validate project key	Checks if the provided project key is valid and not in use.	GET /rest/api/2/projectvalidate/key

Get project key	Returns a valid project key.	GET /rest/api/2/projectvalidate/validProjectKey
Get project name	Returns a valid project name.	GET /rest/api/2/projectvalidate/validProjectName

Project key and name validation (version 3)

Name	Description	API docs link
Validate project key	Checks if the provided project key is valid and not in use.	GET /rest/api/3/projectvalidate/key
Get project key	Returns a valid project key.	GET /rest/api/3/projectvalidate/validProjectKey
Get project name	Returns a valid project name.	GET /rest/api/3/projectvalidate/validProjectName

Project permission schemes (version 2)

Name	Description	API docs link
Get project issue security scheme	Returns the issue security scheme associated with a project.	GET /rest/api/2/project/{projectKeyOrId}/issuesecuritylevelscheme
Get assigned permission scheme	Returns the permission scheme associated with a project.	GET /rest/api/2/project/{projectKeyOrId}/permissionscheme
Assign permission scheme	Assigns a permission scheme to a project.	PUT /rest/api/2/project/{projectKeyOrId}/permissionscheme

Project permission schemes (version 3)

Name	Description	API docs link
Get project issue security scheme	Returns the issue security scheme associated with a project.	GET /rest/api/3/project/{projectKeyOrId}/issuesecuritylevelscheme
Get assigned permission scheme	Returns the permission scheme associated with a project.	GET /rest/api/3/project/{projectKeyOrId}/permissionscheme
Assign permission scheme	Assigns a permission scheme to a project.	PUT /rest/api/3/project/{projectKeyOrId}/permissionscheme

Project properties (version 2)

Name	Description	API docs link
Get project property keys	Returns all project property keys for the provided project.	GET /rest/api/2/project/{projectIdOrKey}/properties
Delete project property	Deletes the provided property from a project.	DELETE /rest/api/2/project/{projectIdOrKey}/properties/{propertyKey}
Get project property	Returns the value of the provided project property.	GET /rest/api/2/project/{projectIdOrKey}/properties/{propertyKey}
Set project property	Sets the value of the provided project property.	PUT /rest/api/2/project/{projectIdOrKey}/properties/{propertyKey}

Project properties (version 3)

Name	Description	API docs link
Get project property keys	Returns all project property keys for the provided project.	GET /rest/api/3/project/{projectIdOrKey}/properties
Get project property	Returns the value of the provided project property.	GET /rest/api/3/project/{projectIdOrKey}/properties/{propertyKey}
Set project property	Sets the value of the provided project property.	PUT /rest/api/3/project/{projectIdOrKey}/properties/{propertyKey}
Delete project property	Deletes the provided property from a project.	DELETE /rest/api/3/project/{projectIdOrKey}/properties/{propertyKey}

Project role actors (version 2)

Name	Description	API docs link
Delete actors from project role	Deletes actors from a project role.	DELETE /rest/api/2/project/{projectIdOrKey}/role/{id}
Add actors to project role	Adds actors to a project role.	POST /rest/api/2/project/{projectIdOrKey}/role/{id}
Set actors for project role	Sets the actors for a project role, replacing all existing actors.	PUT /rest/api/2/project/{projectIdOrKey}/role/{id}
Delete default actors from project role	Deletes a user or a group of users as default actors from a project role.	DELETE /rest/api/2/role/{id}/actors
Get default actors for project role	Returns a list of the default actors for the provided project role.	GET /rest/api/2/role/{id}/actors
Add default actors to project role	Adds a user or a group of users as default actors to a project role.	POST /rest/api/2/role/{id}/actors

Project role actors (version 3)

Name	Description	API docs link
Set actors for project role	Sets the actors for a project role, replacing all existing actors.	PUT /rest/api/3/project/{projectIdOrKey}/role/{id}
Add actors to project role	Adds actors to a project role.	POST /rest/api/3/project/{projectIdOrKey}/role/{id}
Delete actors from project role	Deletes actors from a project role.	DELETE /rest/api/3/project/{projectIdOrKey}/role/{id}
Get default actors for project role	Returns a list of the default actors for the provided project role.	GET /rest/api/3/role/{id}/actors
Add default actors to project role	Adds a user or a group of users as default actors to a project role.	POST /rest/api/3/role/{id}/actors
Delete default actors from project role	Deletes a user or a group of users as default actors from a project role.	DELETE /rest/api/3/role/{id}/actors

Project roles (version 2)

Name	Description	API docs link
Get project roles for project	Returns a list of project roles for the provided project.	GET /rest/api/2/project/{projectIdOrKey}/role
Get project role for project	Returns the details of a project role and a list of actors associated with that role.	GET /rest/api/2/project/{projectIdOrKey}/role/{id}
Get all project roles	Returns a list of all project roles along with their details and default actors.	GET /rest/api/2/role
Create project role	Creates a project role without assigning any actors to it.	POST /rest/api/2/role
Delete project role	Deletes a project role.	DELETE /rest/api/2/role/{id}
Get project role by ID	Returns the details of a project role and a list of the default actors associated with that role based on the provided role ID.	GET /rest/api/2/role/{id}
Update project role name or description	Updates either the name or the description of a project role.	POST /rest/api/2/role/{id}
Update project role name and description	Updates both the name and the description of a project role.	PUT /rest/api/2/role/{id}

Project roles (version 3)

Name	Description	API docs link
------	-------------	---------------

Get project roles for project	Returns a list of project roles for the provided project.	GET /rest/api/3/project/{projectIdOrKey}/role
Get project role for project	Returns the details of a project role and a list of actors associated with that role.	GET /rest/api/3/project/{projectIdOrKey}/role/{id}
Get all project roles	Returns a list of all project roles along with their details and default actors.	GET /rest/api/3/role
Create project role	Creates a project role without assigning any actors to it.	POST /rest/api/3/role
Get project role by ID	Returns the details of a project role and a list of the default actors associated with that role based on the provided role ID.	GET /rest/api/3/role/{id}
Update project role name and description	Updates both the name and the description of a project role.	PUT /rest/api/3/role/{id}
Update project role name or description	Updates either the name or the description of a project role.	POST /rest/api/3/role/{id}
Delete project role	Deletes a project role.	DELETE /rest/api/3/role/{id}

Project types (version 2)

Name	Description	API docs link
Get all project types	Returns all project types regardless of license status.	GET /rest/api/2/project/type
Get licensed project types	Returns all project types with a valid license.	GET /rest/api/2/project/type/accessible
Get project type by key	Returns a project type based on the provided key.	GET /rest/api/2/project/type/{projectTypeKey}
Get accessible project type by key	Returns a project type based on the provided project key, if the provided user has access to the project.	GET /rest/api/2/project/type/{projectTypeKey}/accessible

Project types (version 3)

Name	Description	API docs link
Get all project types	Returns all project types regardless of license status.	GET /rest/api/3/project/type
Get licensed project types	Returns all project types with a valid license.	GET /rest/api/3/project/type/accessible
Get project type by key	Returns a project type based on the provided key.	GET /rest/api/3/project/type/{projectTypeKey}

Get accessible project type by key	Returns a project type based on the provided project key, if the provided user has access to the project.	GET /rest/api/3/project/type/{projectTypeKey}/accessible
------------------------------------	---	---

Project versions (version 2)

Name	Description	API docs link
Get project versions	Returns a list of all versions in a project.	GET /rest/api/2/project/{projectIdOrKey}/versions
Create a new project version	Creates a new project version.	POST /rest/api/2/version
Move a project version	Moves the version's sequence within the project, which alters the display order when viewing a list of versions of the project.	POST /rest/api/2/version/{id}/move
Get a project version's related issues count	Returns some "related issues" statistics for this version. Counts returned are the number of issues that specify this version as their fix version, the number of issues that specify this version as an affected version, and the number of issues where a custom version field is set to this version.	GET /rest/api/2/version/{id}/relatedIssueCounts
Get related work	Returns related work items for the given version ID.	GET /rest/api/2/version/{id}/relatedwork
Create related work	Create a related work item for the given version.	POST /rest/api/2/version/{id}/relatedwork
Update related work	Updates the specified related work.	PUT /rest/api/2/version/{id}/relatedwork
Delete related work	Deletes the specified related work for the specified version.	DELETE /rest/api/2/version/{versionId}/relatedwork/{relatedWorkId}

Project versions (version 3)

Name	Description	API docs link
Get project versions	Returns a list of all versions in a project.	GET /rest/api/3/project/{projectIdOrKey}/versions
Create a new project version	Creates a new project version.	POST /rest/api/3/version

Move a project version	Moves the version's sequence within the project, which alters the display order when viewing a list of versions of the project.	POST /rest/api/3/version/{id}/move
Get a project version's related issues count	Returns some "related issues" statistics for this version. Counts returned are the number of issues that specify this version as their fix version, the number of issues that specify this version as an affected version, and the number of issues where a custom version field is set to this version.	GET /rest/api/3/version/{id}/relatedIssueCounts
Get related work	Returns related work items for the given version ID.	GET /rest/api/3/version/{id}/relatedwork
Update related work	Updates the specified related work.	PUT /rest/api/3/version/{id}/relatedwork
Create related work	Create a related work item for the given version.	POST /rest/api/3/version/{id}/relatedwork
Delete related work	Deletes the specified related work for the specified version.	DELETE /rest/api/3/version/{versionId}/relatedwork/{relatedWorkId}

Projects (version 2)

Name	Description	API docs link
Archive project	Archives a project.	POST /rest/api/2/project/{projectIdOrKey}/archive
Restore deleted or archived project	Restores a project that has been archived or placed in the Jira recycle bin.	POST /rest/api/2/project/{projectIdOrKey}/restore
Get all statuses for project	Returns all valid statuses for a project.	GET /rest/api/2/project/{projectIdOrKey}/statuses
Get project issue type hierarchy DEPRECATED	Returns the issue type hierarchy for a next-gen project.	GET /rest/api/2/project/{projectId}/hierarchy
Get project notification scheme	Returns the notification scheme associated with a project.	GET /rest/api/2/project/{projectKeyOrId}/notificationscheme

Projects (version 3)

Name	Description	API docs link
------	-------------	---------------

Archive project	Archives a project.	POST /rest/api/3/project/{projectIdOrKey}/archive
Restore deleted or archived project	Restores a project that has been archived or placed in the Jira recycle bin.	POST /rest/api/3/project/{projectIdOrKey}/restore
Get all statuses for project	Returns all valid statuses for a project.	GET /rest/api/3/project/{projectIdOrKey}/statuses
Get project issue type hierarchy DEPRECATED	Returns the issue type hierarchy for a next-gen project.	GET /rest/api/3/project/{projectId}/hierarchy
Get project notification scheme	Returns the notification scheme associated with a project.	GET /rest/api/3/project/{projectKeyOrId}/notificationscheme

Screen schemes (version 2)

Name	Description	API docs link
Get screen schemes	Gets the screen schemes for a classic project. Screen schemes allow different screens to be defined depending on the user's activity: creating, editing, or viewing issue data.	GET /rest/api/2/screenscheme
Create a screen scheme	Creates a screen schema that specifies the screens used to display issue data when a user creates, edits, or views issue data.	POST /rest/api/2/screenscheme
Delete a screen scheme	Deletes a screen scheme.	DELETE /rest/api/2/screenscheme/{screenSchemeId}
Update a screen scheme	Updates a screen scheme that specifies the screens used to display issue data when a user creates, edits, or views issue data.	PUT /rest/api/2/screenscheme/{screenSchemeId}

Screen schemes (version 3)

Name	Description	API docs link
Get screen schemes	Gets the screen schemes for a classic project. Screen schemes allow different screens to be defined depending on the user's activity: creating, editing, or viewing issue data.	GET /rest/api/3/screenscheme
Create a screen scheme	Creates a screen schema that specifies the screens used to display issue data when a user creates, edits, or views issue data.	POST /rest/api/3/screenscheme
Update a screen scheme	Updates a screen scheme that specifies the screens used to display issue data when a user creates, edits, or views issue data.	PUT /rest/api/3/screenscheme/{screenSchemeId}

Delete a screen scheme	Deletes a screen scheme.	DELETE /rest/api/3/screenscheme/{screenSchemeId}
------------------------	--------------------------	---

Screen tab fields (version 2)

Name	Description	API docs link
Get all screen tab fields	Returns the list of all screens for a screen tab.	GET /rest/api/2/screens/{screenId}/tabs/{tabId}/fields
Add screen tab field	Adds a field to a screen tab.	POST /rest/api/2/screens/{screenId}/tabs/{tabId}/fields
Remove screen tab field	Removes a field from a screen tab.	DELETE /rest/api/2/screens/{screenId}/tabs/{tabId}/fields/{id}
Move screen tab field	Moves a screen tab field to a different position on that screen tab.	POST /rest/api/2/screens/{screenId}/tabs/{tabId}/fields/{id}/move

Screen tab fields (version 3)

Name	Description	API docs link
Get all screen tab fields	Returns the list of all screens for a screen tab.	GET /rest/api/3/screens/{screenId}/tabs/{tabId}/fields
Add screen tab field	Adds a field to a screen tab.	POST /rest/api/3/screens/{screenId}/tabs/{tabId}/fields
Remove screen tab field	Removes a field from a screen tab.	DELETE /rest/api/3/screens/{screenId}/tabs/{tabId}/fields/{id}
Move screen tab field	Moves a screen tab field to a different position on that screen tab.	POST /rest/api/3/screens/{screenId}/tabs/{tabId}/fields/{id}/move

Screen tabs (version 2)

Name	Description	API docs link
Get all screen tabs	Returns the list of all tabs for a screen.	GET /rest/api/2/screens/{screenId}/tabs
Create screen tab	Creates a tab for a screen.	POST /rest/api/2/screens/{screenId}/tabs
Delete screen tab	Deletes a screen tab.	DELETE /rest/api/2/screens/{screenId}/tabs/{tabId}
Update screen tab name	Updates the name of a screen tab.	PUT /rest/api/2/screens/{screenId}/tabs/{tabId}
Move a screen tab	Moves a screen tab to a different position in a list of screen tabs.	POST /rest/api/2/screens/{screenId}/tabs/{tabId}/move/{pos}

Screen tabs (version 3)

Name	Description	API docs link
Get all screen tabs	Returns the list of all tabs for a screen.	GET /rest/api/3/screens/{screenId}/tabs
Create screen tab	Creates a tab for a screen.	POST /rest/api/3/screens/{screenId}/tabs
Update screen tab name	Updates the name of a screen tab.	PUT /rest/api/3/screens/{screenId}/tabs/{tabId}
Delete screen tab	Deletes a screen tab.	DELETE /rest/api/3/screens/{screenId}/tabs/{tabId}
Move a screen tab	Moves a screen tab to a different position in a list of screen tabs.	POST /rest/api/3/screens/{screenId}/tabs/{tabId}/move/{pos}

Screens (version 2)

Name	Description	API docs link
Get screens for a field	Returns a list of the screens a field is used on.	GET /rest/api/2/field/{fieldId}/screens
Get screens paginated	Returns a paginated list of all screens.	GET /rest/api/2/screens
Create screen	Creates a screen with a default field tab.	POST /rest/api/2/screens
Add field to default screen	Adds a field to the default tab of the default screen.	POST /rest/api/2/screens/addToDefault/{fieldId}
Delete screen	Deletes a screen.	DELETE /rest/api/2/screens/{screenId}
Update screen	Updates a screen.	PUT /rest/api/2/screens/{screenId}
Get available screen fields	Returns a list of screens that can be added to a tab on the provided screen.	GET /rest/api/2/screens/{screenId}/availableFields

Screens (version 3)

Name	Description	API docs link
Get screens for a field	Returns a list of the screens a field is used on.	GET /rest/api/3/field/{fieldId}/screens
Get screens paginated	Returns a paginated list of all screens.	GET /rest/api/3/screens
Create screen	Creates a screen with a default field tab.	POST /rest/api/3/screens
Add field to default screen	Adds a field to the default tab of the default screen.	POST /rest/api/3/screens/addToDefault/{fieldId}

Update screen	Updates a screen.	PUT /rest/api/3/screens/{screenId}
Delete screen	Deletes a screen.	DELETE /rest/api/3/screens/{screenId}
Get available screen fields	Returns a list of screens that can be added to a tab on the provided screen.	GET /rest/api/3/screens/{screenId}/availableFields

Server info (version 2)

Name	Description	API docs link
Get Jira instance info	Returns information about the Jira instance such as the build number, version number, server date, server timezone, and health checks.	GET /rest/api/2/serverInfo

Server info (version 3)

Name	Description	API docs link
Get Jira instance info	Returns information about the Jira instance such as the build number, version number, server date, server timezone, and health checks.	GET /rest/api/3/serverInfo

Status (version 2)

Name	Description	API docs link
Delete Statuses	Deletes one or more statuses.	DELETE /rest/api/2/statuses
Get statuses	Returns the details of one or more workflow status IDs.	GET /rest/api/2/statuses
Create statuses	Create one or more statuses for a global or project scope. For each status, specifies details like the status category, description, and the issue types, projects, and workflows that can use this status.	POST /rest/api/2/statuses
Update statuses	Update the details of one or more statuses. For each status, you can change details like the workflow status category, name, and description.	PUT /rest/api/2/statuses
Search statuses paginated	Returns a list of statuses that match a status name or project provided by the user.	GET /rest/api/2/statuses/search

Status (version 3)

Name	Description	API docs link
Get statuses	Returns the details of one or more workflow status IDs.	GET /rest/api/3/statuses
Update statuses	Update the details of one or more statuses. For each status, you can change details like the workflow status category, name, and description.	PUT /rest/api/3/statuses
Create statuses	Create one or more statuses for a global or project scope. For each status, specifies details like the status category, description, and the issue types, projects, and workflows that can use this status.	POST /rest/api/3/statuses
Delete statuses	Deletes one or more statuses.	DELETE /rest/api/3/statuses
Search statuses paginated	Returns a list of statuses that match a status name or project provided by the user.	GET /rest/api/3/statuses/search

Tasks (version 2)

Name	Description	API docs link
Get a task	Returns the status of a long-running asynchronous task.	GET /rest/api/2/task/{taskId}
Cancel a task	Cancels a long-running task. Only an administrator or the task creator can cancel a task.	POST /rest/api/2/task/{taskId}/cancel

Tasks (version 3)

Name	Description	API docs link
Get a task	Returns the status of a long-running asynchronous task.	GET /rest/api/3/task/{taskId}
Cancel a task	Cancels a long-running task. Only an administrator or the task creator can cancel a task.	POST /rest/api/3/task/{taskId}/cancel

Time tracking (version 2)

Name	Description	API docs link
Get selected time tracking provider	Returns the time tracking provider selected.	GET /rest/api/2/configuration/timetracking
Select time tracking provider	Selects a time tracking provider.	PUT /rest/api/2/configuration/timetracking

Get all time tracking providers	Returns all time tracking providers.	GET /rest/api/2/configuration/timetracking/list
Get time tracking settings	Returns time tracking settings (for example, time format and default time unit).	GET /rest/api/2/configuration/timetracking/options
Set time tracking settings	Sets the time tracking settings.	PUT /rest/api/2/configuration/timetracking/options

Time tracking (version 3)

Name	Description	API docs link
Get selected time tracking provider	Returns the time tracking provider selected.	GET /rest/api/3/configuration/timetracking
Select time tracking provider	Selects a time tracking provider.	PUT /rest/api/3/configuration/timetracking
Get all time tracking providers	Returns all time tracking providers.	GET /rest/api/3/configuration/timetracking/list
Get time tracking settings	Returns time tracking settings (for example, time format and default time unit).	GET /rest/api/3/configuration/timetracking/options
Set time tracking settings	Sets the time tracking settings.	PUT /rest/api/3/configuration/timetracking/options

UI modifications (apps) (version 2)

Name	Description	API docs link
Get UI modifications	Returns details of UI modifications that allow the app to control how selected Jira fields behave on the following views: global issue create, issue view. For example: hide specific fields or set them as required. UI modifications are used only by Forge apps.	GET /rest/api/2/uiModifications
Create a UI modification	Create a new UI modification for a Forge app.	POST /rest/api/2/uiModifications
Delete a UI modification	Delete a UI modification and all contexts that belong to that UI modification for a Forge app.	DELETE /rest/api/2/uiModifications/{uiModificationId}
Update a UI modification	Update a UI modification for a Forge app.	PUT /rest/api/2/uiModifications/{uiModificationId}

UI modifications (apps) (version 3)

Name	Description	API docs link
Get UI modifications	Returns details of UI modifications that allow the app to control how selected Jira fields behave on the following views: global issue create, issue view. For example: hide specific fields or set them as required. UI modifications are used only by Forge apps.	GET /rest/api/3/uiModifications
Create a UI modification	Create a new UI modification for a Forge app.	POST /rest/api/3/uiModifications
Update a UI modification	Update a UI modification for a Forge app.	PUT /rest/api/3/uiModifications/{uiModificationId}
Delete a UI modification	Delete a UI modification and all contexts that belong to that UI modification for a Forge app.	DELETE /rest/api/3/uiModifications/{uiModificationId}

User properties (version 2)

Name	Description	API docs link
Get a user's property keys	Returns a list of user property keys defined by an integration or app. Only custom properties are returned. Jira user properties are not accessed.	GET /rest/api/2/user/properties
Delete a user property	Deletes a user property defined by an integration or app. Jira user properties cannot be deleted by this function.	DELETE /rest/api/2/user/properties/{propertyKey}
Get a user property	Returns the value of a user property defined by an integration or app. Jira user properties are not returned.	GET /rest/api/2/user/properties/{propertyKey}
Set a user property	Sets the value of a user property defined by an integration or app. Jira user properties cannot be set by this function.	PUT /rest/api/2/user/properties/{propertyKey}

User properties (version 3)

Name	Description	API docs link
Get a user's property keys	Returns a list of user property keys defined by an integration or app. Only custom properties are returned. Jira user properties are not accessed.	GET /rest/api/3/user/properties

Get a user property	Returns the value of a user property defined by an integration or app. Jira user properties are not returned.	GET /rest/api/3/user/properties/{propertyKey}
Set a user property	Sets the value of a user property defined by an integration or app. Jira user properties cannot be set by this function.	PUT /rest/api/3/user/properties/{propertyKey}
Delete a user property	Deletes a user property defined by an integration or app. Jira user properties cannot be deleted by this function.	DELETE /rest/api/3/user/properties/{propertyKey}

User search (version 2)

Name	Description	API docs link
Find users assignable to projects	Returns a list of users who can be assigned issues in one or more projects.	GET /rest/api/2/user/assignable/multiProjectSearch
Find users for picker	Returns a list of users whose attributes such as email address or display name match the specified query term.	GET /rest/api/2/user/picker
Find users	Returns a list of active users that match the specified search criteria. The list contains user details such as name, the groups the user belongs to, their avatar, and email address.	GET /rest/api/2/user/search
Find user keys by query	Returns a list of active users that match the specified search criteria related to their Jira activity. For example, you can list users who are assignees, reporters, watchers, voters, or commenters on specific issues. The returned list contains user keys and account IDs.	GET /rest/api/2/user/search/query/key

User search (version 3)

Name	Description	API docs link
Find users assignable to projects	Returns a list of users who can be assigned issues in one or more projects.	GET /rest/api/3/user/assignable/multiProjectSearch
Find users for picker	Returns a list of users whose attributes such as email address or display name match the specified query term.	GET /rest/api/3/user/picker
Find users	Returns a list of active users that match the specified search criteria. The list contains user details such as name, the groups the user belongs to, their avatar, and email address.	GET /rest/api/3/user/search

Find user keys by query	Returns a list of active users that match the specified search criteria related to their Jira activity. For example, you can list users who are assignees, reporters, watchers, voters, or commenters on specific issues. The returned list contains user keys and account IDs.	GET /rest/api/3/user/search/query/key
-------------------------	---	---------------------------------------

Users (version 2)

Name	Description	API docs link
Delete user	Removes a user.	DELETE /rest/api/2/user
Get a user	Returns information about a Jira user. The fields returned depend on the user's profile and visibility settings.	GET /rest/api/2/user
Create user	Creates a user.	POST /rest/api/2/user
Bulk get users	Returns a list of details for the specified users.	GET /rest/api/2/user/bulk
Get account IDs for users	Returns the account IDs for a list of one or more users.	GET /rest/api/2/user/bulk/migration
Reset user default columns	Resets the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	DELETE /rest/api/2/user/columns
Get user's default columns	Returns the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	GET /rest/api/2/user/columns
Set user default columns	Sets the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	PUT /rest/api/2/user/columns
Get user email	Returns a user email.	GET /rest/api/2/user/email
Get user emails	Returns a list of user emails.	GET /rest/api/2/user/email/bulk
Get user's groups	Returns the Jira groups to which a user belongs.	GET /rest/api/2/user/groups
Get all users (default version)	Returns a list of all users, including active users, inactive users, and previously deleted users, that have an Atlassian account.	GET /rest/api/2/users
Get all users	Returns a list of all users, including active users, inactive users, and previously deleted users, that have an Atlassian account.	GET /rest/api/2/users/search

Users (version 3)

Name	Description	API docs link
Get a user	Returns information about a Jira user. The fields returned depend on the user's profile and visibility settings.	GET /rest/api/3/user
Create user	Creates a user.	POST /rest/api/3/user
Delete user	Removes a user.	DELETE /rest/api/3/user
Bulk get users	Returns a list of details for the specified users.	GET /rest/api/3/user/bulk
Get account IDs for users	Returns the account IDs for a list of one or more users.	GET /rest/api/3/user/bulk/migration
Get user's default columns	Returns the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	GET /rest/api/3/user/columns
Set user default columns	Sets the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	PUT /rest/api/3/user/columns
Reset user default columns	Resets the default columns shown for the specified user when viewing a list of Jira issues in the issue navigator.	DELETE /rest/api/3/user/columns
Get user email	Returns a user email.	GET /rest/api/3/user/email
Get user emails	Returns a list of user emails.	GET /rest/api/3/user/email/bulk
Get user's groups	Returns the Jira groups to which a user belongs.	GET /rest/api/3/user/groups
Get all users (default version)	Returns a list of all users, including active users, inactive users, and previously deleted users, that have an Atlassian account.	GET /rest/api/3/users
Get all users	Returns a list of all users, including active users, inactive users, and previously deleted users, that have an Atlassian account.	GET /rest/api/3/users/search

Webhooks (version 2)

Name	Description	API docs link
Delete webhooks by ID	Deletes a webhook that was registered by this app.	DELETE /rest/api/2/webhook
Get dynamic webhooks for app	Returns a list of the webhooks associated with this app that allow the app to be notified when events such as the Jira issue created event occur in this Jira instance.	GET /rest/api/2/webhook

Register dynamic webhooks	Registers a webhook so that this app can be notified when events such as the Jira issue created event occur in this Jira instance.	POST /rest/api/2/webhook
Get failed webhooks	Returns webhooks that have recently failed to be delivered to the requesting app after the specified number of retries.	GET /rest/api/2/webhook/failed
Extend webhook life	Extends the life of a previously-registered webhook so that it can continue to be used. When a webhook is registered, it can be used for 30 days. To keep the webhook active, the app must call this API at least every 30 days to ensure that the webhook stays operational.	PUT /rest/api/2/webhook/refresh

Webhooks (version 3)

Name	Description	API docs link
Get dynamic webhooks for app	Returns a list of the webhooks associated with this app that allow the app to be notified when events such as the Jira issue created event occur in this Jira instance.	GET /rest/api/3/webhook
Register dynamic webhooks	Registers a webhook so that this app can be notified when events such as the Jira issue created event occur in this Jira instance.	POST /rest/api/3/webhook
Delete webhooks by ID	Deletes a webhook that was registered by this app.	DELETE /rest/api/3/webhook
Get failed webhooks	Returns webhooks that have recently failed to be delivered to the requesting app after the specified number of retries.	GET /rest/api/3/webhook/failed
Extend webhook life	Extends the life of a previously-registered webhook so that it can continue to be used. When a webhook is registered, it can be used for 30 days. To keep the webhook active, the app must call this API at least every 30 days to ensure that the webhook stays operational.	PUT /rest/api/3/webhook/refresh

Workflow scheme drafts (version 2)

Name	Description	API docs link
Create draft workflow scheme	Create a draft workflow scheme from an active workflow scheme, by copying the active workflow scheme.	POST /rest/api/2/workflowscheme/{id}/createdraft
Delete draft workflow scheme	Deletes a draft workflow scheme.	DELETE /rest/api/2/workflowscheme/{id}/draft
Get draft workflow scheme	Returns the draft workflow scheme for the specified active workflow scheme.	GET /rest/api/2/workflowscheme/{id}/draft

Update draft workflow scheme	Updates the details of the draft workflow scheme for the specified active workflow scheme.	PUT /rest/api/2/workflowscheme/{id}/draft
Delete draft default workflow	Resets the draft workflow scheme's default workflow to the Jira system workflow.	DELETE /rest/api/2/workflowscheme/{id}/draft/default
Get draft default workflow	Returns the default workflow for a draft workflow scheme.	GET /rest/api/2/workflowscheme/{id}/draft/default
Update draft default workflow	Updates the default workflow for a draft workflow scheme.	PUT /rest/api/2/workflowscheme/{id}/draft/default
Delete workflow for issue type in draft workflow scheme	Deletes the issue type-workflow mapping for an issue type in a workflow scheme's draft.	DELETE /rest/api/2/workflowscheme/{id}/draft/issuetype/{issueType}
Get workflow for issue type in draft workflow scheme	Returns the issue type-workflow mapping for an issue type in a workflow scheme's draft.	GET /rest/api/2/workflowscheme/{id}/draft/issuetype/{issueType}
Set workflow for issue type in draft workflow scheme	Sets the workflow for an issue type in a workflow scheme's draft.	PUT /rest/api/2/workflowscheme/{id}/draft/issuetype/{issueType}
Publish draft workflow scheme	Publishes a draft workflow scheme, by ID.	POST /rest/api/2/workflowscheme/{id}/draft/publish
Delete issue types for workflow in draft workflow scheme	Deletes the workflow-issue type mapping for a workflow in a workflow scheme's draft.	DELETE /rest/api/2/workflowscheme/{id}/draft/workflow
Get issue types for workflows in draft workflow scheme	Returns the workflow-issue type mappings for a workflow scheme's draft.	GET /rest/api/2/workflowscheme/{id}/draft/workflow
Set issue types for workflow in workflow scheme	Sets the issue types for a workflow in a workflow scheme's draft.	PUT /rest/api/2/workflowscheme/{id}/draft/workflow

Workflow scheme drafts (version 3)

Name	Description	API docs link
Create draft workflow scheme	Create a draft workflow scheme from an active workflow scheme, by copying the active workflow scheme.	POST /rest/api/3/workflowscheme/{id}/createdraft
Get draft workflow scheme	Returns the draft workflow scheme for the specified active workflow scheme.	GET /rest/api/3/workflowscheme/{id}/draft
Update draft workflow scheme	Updates the details of the draft workflow scheme for the specified active workflow scheme.	PUT /rest/api/3/workflowscheme/{id}/draft
Delete draft workflow scheme	Deletes a draft workflow scheme.	DELETE /rest/api/3/workflowscheme/{id}/draft

Get draft default workflow	Returns the default workflow for a draft workflow scheme.	GET /rest/api/3/workflowscheme/{id}/draft/default
Update draft default workflow	Updates the default workflow for a draft workflow scheme.	PUT /rest/api/3/workflowscheme/{id}/draft/default
Delete draft default workflow	Resets the draft workflow scheme's default workflow to the Jira system workflow.	DELETE /rest/api/3/workflowscheme/{id}/draft/default
Get workflow for issue type in draft workflow scheme	Returns the issue type-workflow mapping for an issue type in a workflow scheme's draft.	GET /rest/api/3/workflowscheme/{id}/draft/issuetype/{issueType}
Set workflow for issue type in draft workflow scheme	Sets the workflow for an issue type in a workflow scheme's draft.	PUT /rest/api/3/workflowscheme/{id}/draft/issuetype/{issueType}
Delete workflow for issue type in draft workflow scheme	Deletes the issue type-workflow mapping for an issue type in a workflow scheme's draft.	DELETE /rest/api/3/workflowscheme/{id}/draft/issuetype/{issueType}
Publish draft workflow scheme	Publishes a draft workflow scheme, by ID.	POST /rest/api/3/workflowscheme/{id}/draft/publish
Get issue types for workflows in draft workflow scheme	Returns the workflow-issue type mappings for a workflow scheme's draft.	GET /rest/api/3/workflowscheme/{id}/draft/workflow
Set issue types for workflow in workflow scheme	Sets the issue types for a workflow in a workflow scheme's draft.	PUT /rest/api/3/workflowscheme/{id}/draft/workflow
Delete issue types for workflow in draft workflow scheme	Deletes the workflow-issue type mapping for a workflow in a workflow scheme's draft.	DELETE /rest/api/3/workflowscheme/{id}/draft/workflow

Workflow scheme project associations (version 2)

Name	Description	API docs link
Get workflow scheme project associations	Returns a list of the workflow schemes associated with a list of projects.	GET /rest/api/2/workflowscheme/project
Assign workflow scheme to project	Assigns a workflow scheme to a classic project that has no issues.	PUT /rest/api/2/workflowscheme/project

Workflow scheme project associations (version 3)

Name	Description	API docs link
Get workflow scheme project associations	Returns a list of the workflow schemes associated with a list of projects.	GET /rest/api/3/workflowscheme/project
Assign workflow scheme to project	Assigns a workflow scheme to a classic project that has no issues.	PUT /rest/api/3/workflowscheme/project

Workflow schemes (version 2)

Name	Description	API docs link
Get all workflow schemes	Returns a list of all workflow schemes, not including draft workflow schemes.	GET /rest/api/2/workflowscheme
Create workflow scheme	Creates a workflow scheme.	POST /rest/api/2/workflowscheme
Bulk get workflow schemes	Returns a list of workflow schemes.	POST /rest/api/2/workflowscheme/read
Update workflow scheme	Updates the configuration of company-managed and team-managed project workflow schemes, such as the mapping of issue types to workflows, and the default workflow used for issues with an issue type that does not have an associated workflow.	POST /rest/api/2/workflowscheme/update
Get required status mappings for workflow scheme update	Returns the status mappings that will be required when the specified workflow scheme is updated to assign the specified workflow to a list of issue types.	POST /rest/api/2/workflowscheme/update/mappings
Delete workflow scheme	Delete a workflow scheme that is not in use by any projects.	DELETE /rest/api/2/workflowscheme/{id}
Get workflow scheme	Returns the details of a workflow scheme, such as a list of issue types and the workflow used for each one.	GET /rest/api/2/workflowscheme/{id}
Classic update workflow scheme	Updates the details of a company-managed project workflow scheme.	PUT /rest/api/2/workflowscheme/{id}
Delete default workflow	Resets the workflow scheme's default workflow to the Jira system workflow.	DELETE /rest/api/2/workflowscheme/{id}/default
Get default workflow	Returns a workflow scheme's default workflow that is used for issue types that are not associated with a workflow in that workflow scheme.	GET /rest/api/2/workflowscheme/{id}/default
Update default workflow	Updates the default workflow for a workflow scheme.	PUT /rest/api/2/workflowscheme/{id}/default
Delete workflow for issue type in workflow scheme	Deletes the issue type-workflow mapping for an issue type in a workflow scheme.	DELETE /rest/api/2/workflowscheme/{id}/issuetype/{issueType}

Get workflow for issue type in workflow scheme	Returns the issue type-workflow mapping for an issue type in a workflow scheme.	GET /rest/api/2/workflowscheme/{id}/issuetype/{issueType}
Set workflow for issue type in workflow scheme	Sets the workflow for an issue type in a workflow scheme.	PUT /rest/api/2/workflowscheme/{id}/issuetype/{issueType}
Delete issue types for workflow in workflow scheme	Deletes the workflow-issue type mapping for a workflow in a workflow scheme.	DELETE /rest/api/2/workflowscheme/{id}/workflow
Get issue types for workflows in workflow scheme	Returns the workflow-issue type mappings for a workflow scheme.	GET /rest/api/2/workflowscheme/{id}/workflow
Set issue types for workflow in workflow scheme	Sets the issue types for a workflow in a workflow scheme.	PUT /rest/api/2/workflowscheme/{id}/workflow

Workflow schemes (version 3)

Name	Description	API docs link
Get all workflow schemes	Returns a list of all workflow schemes, not including draft workflow schemes.	GET /rest/api/3/workflowscheme
Create workflow scheme	Creates a workflow scheme.	POST /rest/api/3/workflowscheme
Get workflow scheme	Returns the details of a workflow scheme, such as a list of issue types and the workflow used for each one.	GET /rest/api/3/workflowscheme/{id}
Classic update workflow scheme	Updates the details of a company-managed project workflow scheme.	PUT /rest/api/3/workflowscheme/{id}
Delete workflow scheme	Delete a workflow scheme that is not in use by any projects.	DELETE /rest/api/3/workflowscheme/{id}
Get default workflow	Returns a workflow scheme's default workflow that is used for issue types that are not associated with a workflow in that workflow scheme.	GET /rest/api/3/workflowscheme/{id}/default

Update default workflow	Updates the default workflow for a workflow scheme.	PUT /rest/api/3/workflowscheme/{id}/default
Delete default workflow	Resets the workflow scheme's default workflow to the Jira system workflow.	DELETE /rest/api/3/workflowscheme/{id}/default
Get workflow for issue type in workflow scheme	Returns the issue type-workflow mapping for an issue type in a workflow scheme.	GET /rest/api/3/workflowscheme/{id}/issuetype/{issueType}
Set workflow for issue type in workflow scheme	Sets the workflow for an issue type in a workflow scheme.	PUT /rest/api/3/workflowscheme/{id}/issuetype/{issueType}
Delete workflow for issue type in workflow scheme	Deletes the issue type-workflow mapping for an issue type in a workflow scheme.	DELETE /rest/api/3/workflowscheme/{id}/issuetype/{issueType}
Get issue types for workflows in workflow scheme	Returns the workflow-issue type mappings for a workflow scheme.	GET /rest/api/3/workflowscheme/{id}/workflow
Set issue types for workflow in workflow scheme	Sets the issue types for a workflow in a workflow scheme.	PUT /rest/api/3/workflowscheme/{id}/workflow
Delete issue types for workflow in workflow scheme	Deletes the workflow-issue type mapping for a workflow in a workflow scheme.	DELETE /rest/api/3/workflowscheme/{id}/workflow
Bulk get workflow schemes	Returns a list of workflow schemes.	POST /rest/api/3/workflowscheme/read
Update workflow scheme	Updates the configuration of company-managed and team-managed project workflow schemes, such as the mapping of issue types to workflows, and the default workflow used for issues with an issue type that does not have an associated workflow.	POST /rest/api/3/workflowscheme/update
Get required status mappings for workflow scheme update	Returns the status mappings that will be required when the specified workflow scheme is updated to assign the specified workflow to a list of issue types.	POST /rest/api/3/workflowscheme/update/mappings

Workflow status categories (version 2)

Name	Description	API docs link
Get all status categories	Returns a list of all workflow status categories.	GET /rest/api/2/statuscategory
Get a status category	Returns the details of a workflow status category such as its name and the color used to represent that status category.	GET /rest/api/2/statuscategory/{idOrKey}

Workflow status categories (version 3)

Name	Description	API docs link
Get all status categories	Returns a list of all workflow status categories.	GET /rest/api/3/statuscategory
Get a status category	Returns the details of a workflow status category such as its name and the color used to represent that status category.	GET /rest/api/3/statuscategory/{idOrKey}

Workflow statuses (version 2)

Name	Description	API docs link
Get all statuses	Returns a list of all statuses associated with active workflows, and information about those statuses such as their status category.	GET /rest/api/2/status
Get status	Returns the details of a status, such as its status category, that is associated with an active workflow.	GET /rest/api/2/status/{idOrName}

Workflow statuses (version 3)

Name	Description	API docs link
Get all statuses	Returns a list of all statuses associated with active workflows, and information about those statuses such as their status category.	GET /rest/api/3/status
Get status	Returns the details of a status, such as its status category, that is associated with an active workflow.	GET /rest/api/3/status/{idOrName}

Workflow transition properties (version 2)

Name	Description	API docs link
Delete workflow transition property	Deletes a workflow transition property.	DELETE /rest/api/2/workflow/transitions/{transitionId}/properties
Get workflow transition properties	Returns the transition properties used to customize a workflow transition's behavior. An example of when this could be used is to provide multiple translations of text related to the transition.	GET /rest/api/2/workflow/transitions/{transitionId}/properties
Create workflow transition property	Creates a transition property that can be used to customize a workflow transition's behavior. An example of when this could be used is to provide multiple translations of text related to the transition.	POST /rest/api/2/workflow/transitions/{transitionId}/properties
Update workflow transition property	Updates a workflow transition by changing a transition property value.	PUT /rest/api/2/workflow/transitions/{transitionId}/properties

Workflow transition properties (version 3)

Name	Description	API docs link
Get workflow transition properties	Returns the transition properties used to customize a workflow transition's behavior. An example of when this could be used is to provide multiple translations of text related to the transition.	GET /rest/api/3/workflow/transitions/{transitionId}/properties
Update workflow transition property	Updates a workflow transition by changing a transition property value.	PUT /rest/api/3/workflow/transitions/{transitionId}/properties
Create workflow transition property	Creates a transition property that can be used to customize a workflow transition's behavior. An example of when this could be used is to provide multiple translations of text related to the transition.	POST /rest/api/3/workflow/transitions/{transitionId}/properties
Delete workflow transition property	Deletes a workflow transition property.	DELETE /rest/api/3/workflow/transitions/{transitionId}/properties

Workflow transition rules (version 2)

Name	Description	API docs link
Get workflow transition rule configurations	Returns a list of workflows with transition rules.	GET /rest/api/2/workflow/rule/config
Update workflow transition rule configurations	Updates configuration of workflow transition rules.	PUT /rest/api/2/workflow/rule/config

Delete workflow transition rule configurations	Removes configuration of workflow transition rules.	PUT /rest/api/2/workflow/rule/config/delete
--	---	---

Workflow transition rules (version 3)

Name	Description	API docs link
Get workflow transition rule configurations	Returns a list of workflows with transition rules.	GET /rest/api/3/workflow/rule/config
Update workflow transition rule configurations	Updates configuration of workflow transition rules.	PUT /rest/api/3/workflow/rule/config
Delete workflow transition rule configurations	Removes configuration of workflow transition rules.	PUT /rest/api/3/workflow/rule/config/delete
Validate update workflows	Validates the contents of a "bulk update workflow" request to check whether any errors will occur before the bulk update is done.	POST /rest/api/3/workflows/update/validation

Workflows (version 2)

Name	Description	API docs link
Get all workflows DEPRECATED	Returns a list of all workflows, or the specified workflow, in this Jira instance. (Deprecated)	GET /rest/api/2/workflow
Create workflow DEPRECATED	Creates a workflow.	POST /rest/api/2/workflow
Get workflows paginated	Returns a list of all published classic workflows, or a specific public classic workflow.	GET /rest/api/2/workflow/search
Delete inactive workflow	Deletes an inactive workflow. A workflow cannot be deleted if it is a system workflow, or associated with any workflow scheme or draft workflow scheme.	DELETE /rest/api/2/workflow/{entityId}
Bulk get workflows	Returns a list of workflows and related statuses.	POST /rest/api/2/workflows
Get available workflow capabilities	Returns a list of workflow capabilities, including the workflow rules and other information about the workflow.	GET /rest/api/2/workflows/capabilities
Bulk create workflows	Create workflows and related statuses	POST /rest/api/2/workflows/create

Validate create workflows	Validates the contents of a "bulk create workflow" request to check whether any errors will occur before the bulk create is done.	POST /rest/api/2/workflows/create/validation
Bulk update workflows	Updates one or more workflows with the specified list of statuses.	POST /rest/api/2/workflows/update
Validate update workflows	Validates the contents of a "bulk update workflow" request to check whether any errors will occur before the bulk update is done.	POST /rest/api/2/workflows/update/validation

Workflows (version 3)

Name	Description	API docs link
Get all workflows DEPRECATED	Returns a list of all workflows, or the specified workflow, in this Jira instance.	GET /rest/api/3/workflow
Create workflow DEPRECATED	Creates a workflow.	POST /rest/api/3/workflow
Get workflows paginated	Returns a list of all published classic workflows, or a specific public classic workflow.	GET /rest/api/3/workflow/search
Delete inactive workflow	Deletes an inactive workflow. A workflow cannot be deleted if it is a system workflow, or associated with any workflow scheme or draft workflow scheme.	DELETE /rest/api/3/workflow/{entityId}
Bulk get workflows	Returns a list of workflows and related statuses.	POST /rest/api/3/workflows
Get available workflow capabilities	Returns a list of workflow capabilities, including the workflow rules and other information about the workflow.	GET /rest/api/3/workflows/capabilities
Bulk create workflows	Create workflows and related statuses.	POST /rest/api/3/workflows/create
Validate create workflows	Validates the contents of a "bulk create workflow" request to check whether any errors will occur before the bulk create is done.	POST /rest/api/3/workflows/create/validation
Bulk update workflows	Updates one or more workflows with the specified list of statuses.	POST /rest/api/3/workflows/update
Validate update workflows	Validates the contents of a "bulk update workflow" request to check whether any errors will occur before the bulk update is done.	POST /rest/api/3/workflows/update/validation

Jira Software

These APIs are only used by software projects.

Board

Name	Description	API docs link
Get board by filter id	Returns boards based on a filter.	GET /rest/agile/1.0/board/filter/{filterId}
Get a board's property	Returns the value of a board's property.	GET /rest/agile/1.0/board/{boardId}/properties/{propertyKey}
Set a board property	Sets the value of a board's property.	PUT /rest/agile/1.0/board/{boardId}/properties/{propertyKey}
Deletes a board's property	Removes a board's property.	DELETE /rest/agile/1.0/board/{boardId}/properties/{propertyKey}

Board

Name	Description	API docs link
Get details for a sprint	Returns the details of a sprint.	GET /rest/agile/1.0/sprint/{sprintId}
Update a sprint	Updates the sprint exactly as sent.	PUT /rest/agile/1.0/sprint/{sprintId}
Partially update a sprint	Updates the sprint, updating only the field that are sent.	POST /rest/agile/1.0/sprint/{sprintId}
Delete a sprint	Deletes a sprint.	DELETE /rest/agile/1.0/sprint/{sprintId}
Get keys for a properties	Returns the keys of all properties for a sprint.	GET /rest/agile/1.0/sprint/{sprintId}/properties
Get a sprint's property	Returns the value of a sprint's property.	GET /rest/agile/1.0/sprint/{sprintId}/properties/{propertyKey}
Set a sprint's property	Sets the value of a sprint's property.	PUT /rest/agile/1.0/sprint/{sprintId}/properties/{propertyKey}
Delete a sprint's property	Deletes a property from the sprint.	DELETE /rest/agile/1.0/sprint/{sprintId}/properties/{propertyKey}

Jira Service Management

These APIs are only used by service management projects.

Assets

Name	Description	API docs link
Get an asset's workspaces	Returns a list of assets workspace ids.	GET /rest/servicedeskapi/assets/workspace

Get insight workspace	Returns a list of an insight's spaces.	GET /rest/servicedeskapi/insight/workspace
-----------------------	--	--

Customer

Name	Description	API docs link
Create a customer	Adds a customer to Jira Service Management.	POST /rest/servicedeskapi/customer

Info

Name	Description	API docs link
Get info about Jira Service Management	Returns details such as software version, builds and related links for a Jira Service Management instance.	GET /rest/servicedeskapi/info

Knowledge base

Name	Description	API docs link
Get articles matching a query string	Returns articles which match the given query string across all service desks.	GET /rest/servicedeskapi/knowledgebase/article

Organization

Name	Description	API docs link
Get organizations within Jira Service Management	Returns a list of organizations in the Jira Service Management instance.	GET /rest/servicedeskapi/organization
Create an organization	Creates a new organization by name.	POST /rest/servicedeskapi/organization
Get organization details	Returns details of an organization.	GET /rest/servicedeskapi/organization/{organizationId}
Delete an organization	Delete an organization.	DELETE /rest/servicedeskapi/organization/{organizationId}
Get keys of properties	Returns the keys of all properties for an organization.	GET /rest/servicedeskapi/organization/{organizationId}/property

Get property's value	Returns the value of a property from an organization. Examples include organization's attributes, such as phone or email.	GET /rest/servicedeskapi/organization/{organizationId}/property/{propertyKey}
Sets a property's value	Stores a new value against an organization.	PUT /rest/servicedeskapi/organization/{organizationId}/property/{propertyKey}
Delete an organization's property	Removes a property from an organization.	DELETE /rest/servicedeskapi/organization/{organizationId}/property/{propertyKey}
Get users in an organization.	Returns details for all the users associated with an organization.	GET /rest/servicedeskapi/organization/{organizationId}/user
Add user to an organization	Adds one or multiple existing users to an organization.	POST /rest/servicedeskapi/organization/{organizationId}/user
Remove user from an organization	Removes one or multiple users from an organization	DELETE /rest/servicedeskapi/organization/{organizationId}/user

Service desk

Name	Description	API docs link
Get service desks	Returns the details of all the service desks the user has permission to access.	GET /rest/servicedeskapi/servicedesk
Search for articles in service desk's knowledge base	Returns articles which match the given query and belong to the knowledge base linked to the service desk.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/knowledgebase/article
Get property value	Returns the value of a property from a request type.	GET /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}/property/{propertyKey}
Set a request type's property	Sets the value of property of a request type.	PUT /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}/property/{propertyKey}
Delete the property of a request type	Removes a property from a request type.	DELETE /rest/servicedeskapi/servicedesk/{serviceDeskId}/requesttype/{requestTypeId}/property/{propertyKey}