

logicpuzzle.sty

v1.9

A style file for typesetting logic puzzles

4				2
		4	5	
3				

4	3	5	1	2
2	1	3	4	5
5	4	2	3	1
1	2	4	5	3
3	5	1	2	4

April 17, 2013

Package author:
Josef Kleber

1 Supported puzzles	4
1.1 2D-Sudoku	4
1.2 Battleship	4
1.3 Bokkusu	4
1.4 Chaos Sudoku	5
1.5 Hakyuu	5
1.6 Hitori	5
1.7 Kendoku	6
1.8 Killer Sudoku	6
1.9 Laser Beam	6
1.10 Skyline	7
1.11 Slitherlink	7
1.12 Sudoku	7
2 Roll out your own grid-based logic puzzle	8
3 The code	9
3.1 PGF layers	9
3.2 Environments	10
3.2.1 puzzlebackground	10
3.2.2 puzzleforeground	10
3.3 Commands	10
3.3.1 Initialization	10
3.3.1.1 \LP@define@key	10
3.3.1.2 \LP@define@choicekey@fontsize	11
3.3.1.3 \LP@init@counter	11
3.3.2 Drawing grids	11
3.3.2.1 \LP@drawgrid	11
3.3.2.2 \LP@drawsudokugrid	11
3.3.2.3 \LP@drawbackground	11
3.3.3 In the grid	11
3.3.3.1 \setcell	11
3.3.3.2 \setbigcell	11
3.3.3.3 \LP@setcellcontent	12
3.3.3.4 \LP@setcellcontentC	12
3.3.3.5 \setrow	12
3.3.3.6 \LP@setrowcontents	12
3.3.3.7 \setcolorrow	12
3.3.3.8 \setcolumn	12
3.3.3.9 \LP@setcolumncontents	12
3.3.3.10 \setcolorcolumn	12
3.3.3.11 \setrule	13
3.3.3.12 \fillcell	13
3.3.3.13 \fillrow	13
3.3.3.14 \fillcolumn	13
3.3.3.15 \filldiagonals	13
3.3.3.16 \framearea	13
3.3.3.17 \fillarea	13

3.3.3.18	<code>\colorarea</code>	14
3.3.3.19	<code>\framepuzzle</code>	14
3.3.3.20	<code>\tikzpath</code>	14
3.3.3.21	<code>\LP@ingrid</code>	14
3.3.3.22	<code>\LP@definecolor</code>	14
3.3.4	Around the grid	15
3.3.4.1	<code>\LP@leftcolumn</code>	15
3.3.4.2	<code>\LP@rightcolumn</code>	15
3.3.4.3	<code>\LP@toprow</code>	15
3.3.4.4	<code>\LP@bottomrow</code>	15
3.3.5	Presentation	15
3.3.5.1	<code>\titleformat</code>	15
3.3.5.2	<code>\puzzlecounter</code>	15
3.3.5.3	<code>\setpuzzlecounter</code>	15
3.3.5.4	<code>\definecounterstyle</code>	16
3.3.5.5	<code>\setgridlinestyle</code>	16
3.3.5.6	<code>\setnormallinewidth</code>	16
3.3.5.7	<code>\setthicklinewidth</code>	16
3.3.5.8	<code>\LP@drawcounter</code>	16
4	Examples	16
	Index	17

1 Supported puzzles

1.1 2D-Sudoku

1				
3				4
	4		2	
			3	

1	3	4	5	2
3	2	5	1	4
5	4	3	2	1
2	5	1	4	3
4	1	2	3	5

1.2 Battleship

41222

3					
0					
4					
1					
3					

41222

3					
0					
4					
1					
3					

1.3 Bokkusu

	7	1	11	9	6	
5						?
4						13
3						5
2						12
1						2
	1	2	3	4	5	

	7	1	11	9	6	
5						?
4						13
3						5
2						12
1						2
	1	2	3	4	5	

1.4 Chaos Sudoku

4				2
		4	5	
3				

4	3	5	1	2
2	1	3	4	5
5	4	2	3	1
1	2	4	5	3
3	5	1	2	4

1.5 Hakyuu

2		6	5	
			4	
3				
	2			5
			1	

2	3	6	5	4
1	7	3	4	2
3	1	2	1	3
1	2	1	3	5
2	3	4	1	2

1.6 Hitori

2	4	2	1	1
1	3	2	4	1
1	3	3	3	2
4	2	1	3	3
4	1	2	2	3

2	4		1	
	3	2	4	1
1		3		2
4	2	1	3	
	1		2	3

1.7 Kendoku

4+	2÷	75×		2
			2×	
5	60×			1
8×		2−	1−	
			8+	


4+	2÷	75×		2
1	4	3	5	2
3	2	5	2×	4
5	60×		4	2
8×		2−	1−	3
4	1	2	8+	5

1.8 Killer Sudoku

7	6	5	
			6
7			
	9		

7	6	5	
3	2	4	1
4	1	3	2
7		1	3
1	9	2	4

1.9 Laser Beam



1.10 Skyline

			2		3
3	2				3
4				3	1
	3		3		1

			2		3
5	4	3	1	2	
4	5	1	2	3	
3	2	3	5	4	1
4	1	2	4	3	5
3	1	2	5	4	
	3		3		1

1.11 Slitherlink

			3	2	
	3		0		
					2
4			3		0

		3	2		
3		0			
				2	
4		3			0

1.12 Sudoku

	2	6						
						1	7	
		3	1		6			
	6			5		8		3
		9	2	6	1	7		
5		4		8			6	
			8		4	3		
	4	8						
						9	4	

1	2	6	5	7	8	4	3	9
4	8	5	9	3	2	1	7	6
7	9	3	1	4	6	5	8	2
2	6	1	4	5	7	8	9	3
8	3	9	2	6	1	7	5	4
5	7	4	3	8	9	2	6	1
6	5	2	8	9	4	3	1	7
9	4	8	7	1	3	6	2	5
3	1	7	6	2	5	9	4	8

2 Roll out your own grid-based logic puzzle

As an example we take a look at the `bokkusu.sty` package. First, we ignore the LPPL license stuff.

```
\ProvidesPackage{bokkusu}[2013/03/25 bokkusu.sty v1.2 - Josef Kleber (C) 2013]%
\RequirePackage{logicpuzzle}%
```

We wrote a package `bokkusu.sty` with version number `v1.2` and date `2013/03/25` and added a copyright remark. We need to load the code base package `logicpuzzle.sty`.

```
\newcommand*\LP@BK@init@prefix{\LP@BK}%
\newcommand*\LP@BK@init@package{bokkusu}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{rows}{5}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{columns}{5}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{scale}{1}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{counterstyle}{none}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{color}{black}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{bgcolor}{%}
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{width}{6.7cm}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{cvmoffset}{-38pt}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{title}{%}
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{titleindent}{0.75cm}%
\LP@define@key{\LP@BK@init@prefix}{\LP@BK@init@package}{titlewidth}{5.85cm}%
\LP@define@choicekey@fontsize{\LP@BK@init@prefix}{\LP@BK@init@package}{Large}%
\ExecuteOptionsX{rows,columns,width,fontsize,scale,color,bgcolor,cvmoffset,
                 counterstyle,title,titleindent,titlewidth}%
\ProcessOptionsX\relax%
\LP@init@counter{\LP@BK@init@prefix}%
```

We save the package prefix and name in a macro for easy change. Then we define the options for package `bokkusu.sty` and the environment `bokkusu`, which are executed afterwards to create the macros for the option values. In the end, we need to initialize the package counters.

```
\let\valueH\LP@bottomrow%
\let\valueV\LP@leftcolumn%
\let\sumH\LP@toprow%
\let\sumV\LP@rightcolumn%
```

We need numbers around the grid. Therefore, we define some aliases for the existing generic commands.

```
\newcommand*\bokkususetup[1]%
{%
  \setkeys{bokkusu.sty}{#1}%
}%
```

We define `\bokkususetup` for resetting the global package options.

Finally, we define the bokkusu environment.

```
\newenvironment{bokkusu}[1][ ]%
{%
  \setkeys{bokkusu}{#1}%
  \LP@set@package{bokkusu}%
  \LP@set@env@prefix{LP@BK}%
  \setcounter{LP@BK@rows}{\LP@BK@rows}%
  \setcounter{LP@BK@columns}{\LP@BK@columns}%
  \stepcounter{LP@BK@rows}%
  \stepcounter{LP@BK@columns}%
}
```

We locally set the environment options and the prefix and name of the current puzzle environment. We need to reset the counters for rows and columns, as they might have been altered.

```
\begin{minipage}[t]{\LP@BK@width}%
\ifthenelse{\equal{\LP@BK@title}{}}%
{\par\enspace\par}% empty
{\enspace\par\noindent\hspace{\LP@BK@titleindent}\parbox{\LP@BK@titlewidth}
{\strut\LP@titleformat\LP@BK@title}\vspace{3mm}\par}%
\begin{tikzpicture}[scale=\LP@BK@scale]%
  \LP@drawbackground{1}{1}{\LP@BK@columns}{\LP@BK@rows}{\LP@BK@bgcolor}%
  \LP@drawgrid{1}{1}{\LP@BK@columns}{\LP@BK@rows}{1cm}%
}%

```

We start a minipage with width $\langle width \rangle$. If the user defined a title, we typeset the title and add a vertical space. Then, we draw the puzzle with the help of tikz.sty. We start drawing the background and the grid.

```
{%
  \end{tikzpicture}%
  \LP@drawcounter{\LP@BK@counterstyle}%
  \stepcounter{LP@puzzlecounter}%
  \end{minipage}%
}%

```

Finally, we just end the picture for the puzzle. We draw and step the counter. As last action, we need to close the minipage environment. That's it. Easy, isn't it? You just need to copy this skelton and change or add some code for your specific puzzle.

3 The code

3.1 PGF layers

The logicpuzzle.sty package defines the PGF layers: LPdump, LPbgcolor, LPbackgroundtwo, LPbackground, LPforeground and LPforegroundtwo

Without specifying a special layer, the standard main layer is used. The LPbackground and LPforeground layers can be accessed with the puzzlebackground

[see: 3.2.1] and puzzleforeground [see: 3.2.2] environments. The LPbgcolor is and should only be used for the background color of the grid.

All layers can also be accessed with the generic PGF method:

```
\begin{pgfonlayer}{layer}
...
\end{pgfonlayer}{layer}
```

Order: LPdump → LPbgcolor → LPbackgroundtwo → LPbackground → main → LPforeground → LPforegroundtwo

So, if you are in the need to place something behind LPbackground or in front of LPforeground, you can use the LPbackgroundtwo and LPforegroundtwo layers. You can hide elements like help nodes behind the background color on the LPdump layer.

3.2 Environments

3.2.1 puzzlebackground

```
\begin{puzzlebackground}
...
\end{puzzlebackground}
```

The puzzlebackground environment allows you to place elements behind the main layer on the LPbackground layer [see: 3.1]. This is for example usefull for the \fillarea [see: 3.3.3.17] command.

3.2.2 puzzleforeground

```
\begin{puzzleforeground}
...
\end{puzzleforeground}
```

The puzzleforeground environment allows you to place elements in front of the main layer on the LPforeground layer [see: 3.1]. This is for example usefull for the \framearea [see: 3.3.3.16] command.

3.3 Commands

3.3.1 Initialization

3.3.1.1 \LP@define@key

```
\LP@define@key{<prefix>}{<package>}{<option>}{<default>}
```

With the \LP@define@key command, you can define the options of the package *<package>* **and** of the environment *<package>*. A *<prefix>* is needed for creating different name spaces.

```
\LP@define@key{LP@BS}{battleship}{rows}{5}
```

This code snippet defines the option rows as global option for battleship.sty and as local option for environment battleship with the default value 5. This value is stored in \LP@BS@rows.

3.3.1.2 \LP@define@choicekey@fontsize

`\LP@define@choicekey@fontsize
{\langle prefix \rangle}{\langle package \rangle}{\langle default \rangle}`

With the `\LP@define@choicekey@fontsize` command, you can define the choice key option `fontsize` of the package `\langle package \rangle` **and** of the environment `\langle package \rangle`. Possible keys are: `tiny`, `scriptsize`, `footnotesize`, `small`, `normalsize`, `large`, `Large`, `LARGE`, `huge`, `Huge`

3.3.1.3 \LP@init@counter

`\LP@init@counter{\langle prefix \rangle}`

The command `\LP@init@counter` defines the counters `\langle prefix \rangle@rows` and `\langle prefix \rangle@columns`, initialize them with `\langle prefix \rangle@rows` and `\langle prefix \rangle@columns` and steps the counters.

3.3.2 Drawing grids

3.3.2.1 \LP@drawgrid

`\LP@drawgrid{\langle xmin \rangle}{\langle ymin \rangle}
{\langle xmax \rangle}{\langle ymax \rangle}{\langle step \rangle}`

With the `\LP@drawgrid` command, you can draw the grid `(\langle xmin \rangle, \langle ymin \rangle)` to `(\langle xmax \rangle, \langle ymax \rangle)` with step `\langle step \rangle`. For drawing the standard puzzle grid the step must be 1cm.

3.3.2.2 \LP@drawsudokugrid

`\LP@drawsudokugrid`

The command `\LP@drawsudokugrid` draws the standard Sudoku grid, but just the thicker lines. You will have to overlay the standard grid to get a full Sudoku grid.

3.3.2.3 \LP@drawbackground

`\LP@drawbackground{\langle xmin \rangle}
{\langle ymin \rangle}{\langle xmax \rangle}{\langle ymax \rangle}{\langle color \rangle}`

With the `\LP@drawbackground` command, you can draw the background color of the grid.

3.3.3 In the grid

3.3.3.1 \setcell

`\setcell{\langle column \rangle}{\langle row \rangle}
{\langle element \rangle}`

With the `\setcell` command, you can set `\langle element \rangle` into cell `\langle column \rangle \langle row \rangle` as central node. It is aware of the current values of the surrounding environment options `rows`, `columns`, `scale` and `fontsize`. Furthermore, a check if `\langle element \rangle` is within the grid is applied.

3.3.3.2 \setbigcell

`\setbigcell[\langle fontsize \rangle]{\langle column \rangle}
{\langle row \rangle}{\langle element \rangle}`

With the `\setbigcell` command, you can set `\langle element \rangle` into a big (2×2) cell `\langle column \rangle \langle row \rangle` as central node. The optional argument `\langle fontsize \rangle` is set to

'Huge' by default.

3.3.3.3 \LP@setcellcontent

`\LP@LP@setcellcontent{⟨column⟩}{⟨row⟩}{⟨element⟩}` The command `\LP@setcellcontent` is the generic command to set an arbitrary `⟨element⟩`.

3.3.3.4 \LP@setcellcontentC

`\LP@LP@setcellcontentC{⟨column⟩}{⟨row⟩}{⟨element⟩}` The command `\LP@setcellcontentC` is the generic command to set an arbitrary `⟨element⟩` in a centered node in the bottom left corner.

3.3.3.5 \setrow

`\setrow{⟨row⟩}{⟨csv list⟩}` With the `\setrow` command, you can set the contents of a `⟨row⟩`. These may be numbers or letters.

3.3.3.6 \LP@setrowcontents

`\LP@setrowcontents{⟨csv list⟩}{⟨column⟩}{⟨row⟩}` The command `\LP@setrowcontents` is the generic command to set row contents. It does not necessarily start with `⟨column⟩` 1!

3.3.3.7 \setcolorrow

`\setcolorrow{⟨row⟩}{⟨csv list⟩}` With the `\setcolorrow` command, you can set the contents of a `⟨row⟩`. Furthermore, the background of the cell is filled with color `LP@cc@romannumber` [see: 3.3.3.22]. With the number 0, you can black out the grid cell.

3.3.3.8 \setcolumn

`\setcolumn{⟨column⟩}{⟨csv list⟩}` With the `\setcolumn` command, you can set the contents of a `⟨column⟩`. These may be numbers or letters.

3.3.3.9 \LP@setcolumncontents

`\LP@setcolumncontents{⟨csv list⟩}{⟨column⟩}{⟨row⟩}` The command `\LP@setcolumncontents` is the generic command to set column contents. It does not necessarily start with `⟨row⟩` 1!

3.3.3.10 \setcolorcolumn

`\setcolorcolumn{⟨column⟩}{⟨csv list⟩}` With the `\setcolorcolumn` command, you can set the contents of a `⟨column⟩`. Furthermore, the background of the cell is filled with color `LP@cc@romannumber` [see: 3.3.3.22].

3.3.3.11 `\setrule`

`\setrule{<column>}{<row>}{<rule>}` With the `\setrule` command, you can set a calculation rule *<rule>* into the top left corner of cell *<column>**<row>*. The rule is typeset in inline math mode. You might consider using the `\times` and `\div` commands.

3.3.3.12 `\fillcell`

`\fillcell{<column>}{<row>}` With the `\fillcell` command, you can fill cell *<column>**<row>* with the color defined with environment option `color`¹. It is aware of the current values of the surrounding environment options `rows`, `columns`, `scale` and `color`. Furthermore, a check if the cell is within the grid is applied.

3.3.3.13 `\fillrow`

`\fillrow{<row>}{<csv list>}` With the `\fillrow` command, you can fill a *<row>*. In *<csv list>* '1' means 'fill' and '0' means 'don't fill'. Internally, `\fillrow` uses `\fillcell` [see: 3.3.3.12].

3.3.3.14 `\fillcolumn`

`\fillcolumn{<column>}{<csv list>}` With the `\fillcolumn` command, you can fill a *<column>*. In *<csv list>* '1' means 'fill' and '0' means 'don't fill'. Internally, `\fillcolumn` uses `\fillcell` [see: 3.3.3.12].

3.3.3.15 `\filldiagonals`

`\filldiagonals[<color>]` With the `\filldiagonals` command, you can fill the diagonals with the color specified with the optional argument *<color>* (default: yellow!20). Furthermore, it checks for a quadratic grid, otherwise an error message is issued.

3.3.3.16 `\framearea`

`\framearea{<color>}{<tikz path>}` The command `\framearea` frames the area given by *<tikz path>* with color *<color>*. The reference for coordinates is the bottom left corner of the cell.

```
\framearea{green}{(2,2) -- (2,3) -- (3,3) -- (3,2) -- (2,2)}
```

This command will color the frame of the grid cell (2,2) green. You should consider using this command in the `puzzleforeground` [see: 3.2.2] environment.

3.3.3.17 `\fillarea`

`\fillarea{<color>}{<tikz path>}` The command `\fillarea` fills the area given by *<tikz path>* with color *<color>*. The reference for coordinates is the bottom left corner of the cell. You should

¹Therefore, you must define an option `color` in the style file you want to use fill commands

consider using this command in the puzzlebackground [see: 3.2.1] environment.

3.3.3.18 \colorarea

`\colorarea{<color>}{<tikz path>}` The command `\colorarea` fills the area given by `<tikz path>` with color `<color>` – just like `\framearea` without frame.

3.3.3.19 \framepuzzle

`\framepuzzle[<color>]` With the `\framepuzzle` command, you can frame the grid (thicker line) with the color specified with the optional argument `<color>` (default: black).

3.3.3.20 \tikzpath

`\tikzpath{<column>}{<row>}`
`{<csv list>}` With the `\tikzpath` command, you can easily construct a `\tikz` path. You just need to define a starting point `<column>``<row>` (bottom left corner) and a `<csv list>` with direction indicators relative to the current position.

7: up left	8: up	9: up right
4: left	5: no change	6: right
1: down left	2: down	3: down right

```
\framearea{green}{\tikzpath{2}{2}{8,6,2,4}}
```

This command will frame grid cell (2,2) green.

3.3.3.21 \LP@ingrid

`\LP@ingrid`
`{<column>}{<row>}{<max column>}`
`{<max row>}{<package>}` With the `\LP@ingrid` command, you can check if an element – that should be placed – is within the grid. Otherwise an error message is issued.

3.3.3.22 \LP@definecolor

`\LP@definecolor`
`{<name>}{<rgb color>}` With the `\LP@definecolor` command, you can define named rgb colors, especially for defining background colors of numbers used in `\setcolorrow` [see: 3.3.3.7] and `\setcolorcolumn` [see: 3.3.3.10].

The background color names follow the pattern: `LP@c@romannumber`

```
\LP@definecolor{LP@c@iv}{.55,1,.88}
```

This command will define the new background color of number 4!

3.3.4 Around the grid

3.3.4.1 \LP@leftcolumn

`\LP@leftcolumn{\{<csv list>}` With the `\LP@leftcolumn` command, you can set the contents of the column left to the grid. The `skyline.sty` package uses for example:

```
\let\skylineL\LP@leftcolumn
```

3.3.4.2 \LP@rightcolumn

`\LP@rightcolumn{\{<csv list>}` With the `\LP@rightcolumn` command, you can set the contents of the column right to the grid.

3.3.4.3 \LP@toprow

`\LP@toprow{\{<csv list>}` With the `\LP@toprow` command, you can set the contents of the row above the grid.

3.3.4.4 \LP@bottomrow

`\LP@bottomrow{\{<csv list>}` With the `\LP@bottomrow` command, you can set the contents of the row below the grid.

3.3.5 Presentation

3.3.5.1 \titleformat

`\titleformat{\{<format>}` With the `\titleformat` command, you can define the `<format>` of the title. By default, the definition is as follows:

```
\titleformat{\centering\Large\color{blue}}
```

3.3.5.2 \puzzlecounter

`\puzzlecounter` The command `\puzzlecounter` provides the counter in textual form to use it for example in `\definecounterstyle`.

3.3.5.3 \setpuzzlecounter

`\setpuzzlecounter{\{<number>}` With the command `\setpuzzlecounter`, you can reset the puzzle counter, for example before the solutions.

3.3.5.4 \definecounterstyle

`\definecounterstyle{<name>}`
`{<definition>}` The command `\definecounterstyle` allows you to define your own styles. For example, the style `left` is defined as follows:

```
\definecounterstyle{left}{
  \begingroup\reversemarginpar\marginnote{
    \tikz\node[shape=rectangle,fill=yellow!40,inner sep=7pt,
      draw,rounded corners=3pt,thick]
    {\Huge\puzzlecounter};;\LP@cvmoffset}\endgroup
}
```

To typeset the counter into the margin we use the command `\marginnote`. We need to use the command `\reversemarginpar` to set the counter into the left margin. Of course, we must use this command in a group for local scope. Finally we use `\puzzlecounter` in a `\tikz` node with a vertical offset set with the option `cvoffset`.

3.3.5.5 \setgridlinestyle

`\setgridlinestyle{<style>}` The command `\setgridlinestyle` sets the style of lines used in the grid. By default, the style is set to solid, whereas `slitherlink.sty` uses dashed.

3.3.5.6 \setnormallinewidth

`\setnormallinewidth{<dimension>}` With the command `\setnormallinewidth`, you can set the width of the standard lines (default: 0.5pt)

3.3.5.7 \setthicklinewidth

`\setthicklinewidth{<dimension>}` With the command `\setthicklinewidth`, you can set the width of the 'thicker' lines (default: 1.5pt)

3.3.5.8 \LP@drawcounter

`\LP@drawcounter{<name>}` The command `\LP@drawcounter` draws the counter with counter style `<name>`.



4 Examples

You can download application examples and their solutions from the [project page](#). The puzzles are originally licensed under .

B

battleship environment 10
 battleship.sty 10
 bokkusu environment 8, 9
 bokkusu.sty 8
 \bokkususetup 8

C

$\langle color \rangle$ mandatory argument . 11,
 13, 14
 $\langle color \rangle$ optional argument 13, 14
 color style option 13
 \colorarea 14
 $\langle column \rangle$ mandatory argument 11–
 14
 $\langle column \rangle$ optional argument .. 14
 columns style option ... 9, 11, 13
 $\langle csv list \rangle$ mandatory argument 12–
 15
 $\langle csv list \rangle$ optional argument .. 14
 cvoffset style option 16

D

$\langle default \rangle$ mandatory argument 10,
 11
 \definecounterstyle ... 15, 16
 $\langle definition \rangle$ mandatory argument
 16
 $\langle dimension \rangle$ mandatory argument
 16
 \div 13

E

$\langle element \rangle$ mandatory argument 11,
 12
 environment
 battleship 10
 bokkusu 8, 9
 minipage 9
 puzzlebackground 9, 10, 14
 puzzleforeground .. 10, 13

F

\fillarea 10, 13
 \fillcell 13
 \fillcolumn 13
 \filldiagonals 13
 \fillrow 13

$\langle fontsize \rangle$ optional argument .. 11
 fontsize style option 11
 $\langle format \rangle$ mandatory argument 15
 \framearea 10, 13, 14
 \framepuzzle 14

L

logicpuzzle.sty 8, 9
 \LP 10–12, 14–16
 \LP@bottomrow 15
 \LP@BS@rows 10
 \LP@define@choicekey@fontsize
 11
 \LP@define@key 10
 \LP@definecolor 14
 \LP@drawbackground 11
 \LP@drawgrid 11
 \LP@drawsudokugrid 11
 \LP@ingrid 14
 \LP@init@counter 11
 \LP@leftcolumn 15
 \LP@rightcolumn 15
 \LP@setcellcontent 12
 \LP@setcellcontentC 12
 \LP@setcolumncontents 12
 \LP@setrowcontents 12
 \LP@toprow 15
 LPbackground PGF layer .. 9, 10
 LPbackgroundtwo PGF layer 9, 10
 LPbgcolor PGF layer 9, 10
 LPdump PGF layer 9, 10
 LPforeground PGF layer .. 9, 10
 LPforegroundtwo PGF layer 9, 10

M

main PGF layer 9, 10
 mandatory argument
 $\langle color \rangle$ 11, 13, 14
 $\langle column \rangle$ 11–14
 $\langle csv list \rangle$ 12–15
 $\langle default \rangle$ 10, 11
 $\langle definition \rangle$ 16
 $\langle dimension \rangle$ 16
 $\langle element \rangle$ 11, 12
 $\langle format \rangle$ 15
 $\langle max column \rangle$ 14
 $\langle max row \rangle$ 14
 $\langle name \rangle$ 14, 16

- `<number>` 15
 - `<option>` 10
 - `<package>` 10, 11, 14
 - `<prefix>` 10, 11
 - `<rgb color>` 14
 - `<row>` 11–14
 - `<rule>` 13
 - `<step>` 11
 - `<style>` 16
 - `<tikz path>` 13, 14
 - `<width>` 9
 - `<xmax>` 11
 - `<xmin>` 11
 - `<ymax>` 11
 - `<ymin>` 11
 - `\marginnote` 16
 - `<max column>` mandatory argument
..... 14
 - `<max row>` mandatory argument 14
 - minipage environment 9
- N**
- `<name>` mandatory argument 14,
16
 - `<number>` mandatory argument 15
- O**
- `<option>` mandatory argument 10
 - optional argument
 - `<color>` 13, 14
 - `<column>` 14
 - `<csv list>` 14
 - `<fontsize>` 11
 - `<row>` 14
- P**
- `<package>` mandatory argument 10,
11, 14
 - PGF layer
 - LPbackground 9, 10
 - LPbackgroundtwo 9, 10
 - LPbgcolor 9, 10
 - LPdump 9, 10
 - LPforeground 9, 10
 - LPforegroundtwo 9, 10
 - main 9, 10
 - `<prefix>` mandatory argument 10,
11
 - puzzlebackground environment 9,
10, 14
 - `\puzzlecounter` 15, 16
 - puzzleforeground environment .
..... 10, 13
- R**
- `\reversemarginpar` 16
 - `<rgb color>` mandatory argument
..... 14
 - `<row>` mandatory argument 11–14
 - `<row>` optional argument 14
 - rows style option 9–11, 13
 - `<rule>` mandatory argument .. 13
- S**
- scale style option 11, 13
 - `\setbigcell` 11
 - `\setcell` 11
 - `\setcolorcolumn` 12, 14
 - `\setcolorrow` 12, 14
 - `\setcolumn` 12
 - `\setgridlinestyle` 16
 - `\setnormallinewidth` 16
 - `\setpuzzlecounter` 15
 - `\setrow` 12
 - `\setrule` 13
 - `\setthicklinewidth` 16
 - skyline.sty 15
 - slitherlink.sty 16
 - `<step>` mandatory argument .. 11
 - `<style>` mandatory argument . 16
 - style option
 - color 13
 - columns 9, 11, 13
 - cvoffset 16
 - fontsize 11
 - rows 9–11, 13
 - scale 11, 13
- T**
- `\tikz` 14, 16
 - `<tikz path>` mandatory argument
..... 13, 14
 - tikz.sty 9
 - `\tikzpath` 14
 - `\times` 13
 - `\titleformat` 15

W

$\langle width \rangle$ mandatory argument . . 9

X

$\langle xmax \rangle$ mandatory argument . . 11

$\langle xmin \rangle$ mandatory argument . . 11

Y

$\langle ymax \rangle$ mandatory argument . . 11

$\langle ymin \rangle$ mandatory argument . . 11