

A Minimal Demo of knitr

Yihui Xie

January 6, 2013

You can test if **knitr** works with this minimal demo. OK, let's get started with some boring random numbers:

```
set.seed(1121)
(x <- rnorm(20))

## [1] 0.14496 0.43832 0.15319 1.08494 1.99954 -0.81188 0.16027 0.58589 0.36009
## [10] -0.02531 0.15088 0.11008 1.35968 -0.32699 -0.71638 1.80977 0.50840 -0.52746
## [19] 0.13272 -0.15594

mean(x)


## [1] 0.3217

var(x)

## [1] 0.5715
```

The first element of `x` is 0.145. Boring boxplots and histograms recorded by the PDF device:

```
## two plots side by side (option fig.show='hold')
par(mar = c(4, 4, 0.1, 0.1), cex.lab = 0.95, cex.axis = 0.9, mgp = c(2, 0.7, 0), tcl = -0.3,
     las = 1)
boxplot(x)
hist(x, main = "")
```



Do the above chunks work? You should be able to compile the TeX document and get a PDF file like this one: <https://github.com/downloads/yihui/knitr/knitr-minimal.pdf>. The Rnw source of this document is at <https://github.com/yihui/knitr/blob/master/inst/examples/knitr-minimal.Rnw>.